

ISO 12219-5:2014-05 (E)

Interior air of road vehicles - Part 5: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Static chamber method

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Principle	3
5	Instrument and reagent	3
5.1	General	3
5.2	Test chamber	4
5.3	Clean air	4
5.4	Buffer bag	4
5.5	Non-emitting cover	4
5.6	Vapour sampling devices	5
6	Unit component sample preparation	5
6.1	General	5
6.2	History of the unit component	5
6.3	Packaging, transport and storage of the unit component	5
6.4	Preparation of unit component specimens	6
7	Verification of test conditions	6
7.1	Test temperature	6
7.2	Recovery	6
7.3	Clean air	6
7.4	Background concentration levels	6
7.5	Airtightness	7
8	Standard test procedure	7
8.1	General	7
8.2	Cleaning	8
8.3	Test	8
8.4	Vapour sample collection	9
8.5	Sealing the vapour sampling devices after vapour sample collection	9
8.6	Sample analysis	10
9	Calculation of unit component values	10
10	Test report	10
11	Quality assurance/quality control (QA/QC)	11
12	Safety measures	12

Annex A (informative) General description of the static test chamber	13
Annex B (informative) Example of airtightness test and temperature stability of entire phases	14
Annex C (informative) Comparison of VOCs concentration between the buffer bag inside and the static chamber inside	16
Annex D (informative) A dynamic mode operation	17
Annex E (informative) Comparison of the static mode and the dynamic mode operation	19
Annex F (informative) Correlation between the assembly-based method (ISO 12219-4) and the unit component-based method (ISO 12219-5)	20
Annex G (informative) Correlation between the unit component-based method (ISO 12219-5) and the material-base method (ISO 12219-3)	22
Bibliography	24