

DIN EN 16738:2016-04 (E)

Emission safety of combustible air fresheners - Test methods

| Contents | Page |
|---|------|
| European foreword | 3 |
| 1 Scope | 4 |
| 2 Normative references | 4 |
| 3 Terms and definitions | 5 |
| 4 Test methods | 6 |
| 4.1 Principles | 6 |
| 4.2 Apparatus | 7 |
| 4.3 General test conditions | 7 |
| 4.3.1 General | 7 |
| 4.3.2 Test chamber volume | 7 |
| 4.3.3 Number of test specimens at the same time in the test chamber | 7 |
| 4.3.4 Positioning of test specimens in the test chamber | 8 |
| 4.3.5 Air supply quality and background concentration | 9 |
| 4.3.6 Test specimen preparation and ignition | 9 |
| 4.3.7 Temperature inside the test chamber during the test | 10 |
| 4.3.8 Relative air humidity inside the test chamber during the test | 10 |
| 4.3.9 Oxygen concentration inside the test chamber during the test | 10 |
| 4.3.10 Control of the burning process | 10 |
| 4.3.11 Burn rates | 11 |
| 4.3.12 Sampling and analysis of VOC (benzene, naphthalene) | 11 |
| 4.3.13 Sampling and analysis of formaldehyde | 11 |
| 4.3.14 Sampling and analysis of NO ₂ (nitrogen dioxide) | 12 |
| 4.3.15 Sampling and analysis of SO ₂ (sulfur dioxide) | 12 |
| 4.3.16 Sampling analysis of CO | 12 |
| 4.4 Procedures of testing | 12 |
| 4.5 Calculation of results | 12 |
| 5 Test report | 13 |
| Annex A (informative) Description of sorbent types | 14 |
| Bibliography | 15 |