

ISO 22262-3:2016-10 (E)

Air quality - Bulk materials - Part 3: Quantitative determination of asbestos by X-ray diffraction method

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Range | 3 |
| 5 | Limit of quantification | 3 |
| 6 | Symbols and abbreviated terms | 4 |
| 7 | Requirements for quantification | 4 |
| 8 | Apparatus and reagents | 5 |
| 8.1 | Apparatus | 5 |
| 8.2 | Reagents | 6 |
| 9 | Quantitative XRD method and principle | 7 |
| 9.1 | Quantitative XRD methods using an external standard | 7 |
| 9.2 | Summary of the quantitative method | 7 |
| 9.3 | Preparation of working curve and measurement | 8 |
| 9.4 | Interference minerals | 9 |
| 10 | Preparation of comminuted sample | 9 |
| 10.1 | Preparation of comminuted sample from original sample | 9 |
| 10.2 | Heat treatment of comminuted samples that contain organic constituents | 9 |
| 10.3 | Pretreatment for preparation of residual samples | 10 |
| 10.4 | Preparation of sub-residual samples | 11 |
| 11 | Diffraction peaks for analysis of asbestos and of interference materials | 11 |
| 11.1 | Diffraction peaks for quantitative analysis of asbestos | 11 |
| 11.2 | Interference minerals | 15 |
| 11.2.1 | Possible interference minerals | 15 |
| 11.2.2 | Mass reduction treatments for dissolving interference minerals | 16 |
| 12 | Quantitative analysis by XRD employing substrate standard mass absorption correction | 16 |
| 12.1 | General | 16 |
| 12.2 | Preparation of working curve | 17 |
| 12.2.1 | Preparation of working curve I | 17 |
| 12.2.2 | Preparation of working curve II | 17 |
| 12.3 | Procedure for quantitative analysis | 18 |
| 12.4 | Calculation of asbestos mass fraction | 18 |
| 12.4.1 | Calculation of asbestos mass fraction from a residual sample | 18 |
| 12.4.2 | Calculation of the asbestos mass fraction from a sub-residual sample | 19 |
| 12.5 | Lower limits of detection and quantitative determination for the working curve | 19 |
| 12.6 | Evaluation of uncertainty of XRD measurement | 20 |

| | | |
|----|--|----|
| 13 | Test report | 20 |
| | Annex A (normative) X-ray diffractometer parameters for quantitative analysis of asbestos | 22 |
| | Annex B (normative) Substrate standard mass absorption correction for asbestos quantification | 26 |
| | Annex C (informative) Types of commercial asbestos-containing materials and optimum analytical procedures | 27 |
| | Annex D (informative) Effects of matrix reduction methods | 38 |
| | Annex E (informative) Range of typical detection limits and evaluation of uncertainty of quantitative XRD measurements by XRD method | 41 |
| | Bibliography | 45 |