ISO/TS 20593:2017-06 (E)

Ambient air - Determination of the mass concentration of tire and road wear particles (TRWP) - Pyrolysis-GC-MS method

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and abbreviated terms 3
4.1 Symbols of units (see also ISO 4226) 3
4.2 Abbreviated terms 3

5 Principle 4

6 Reagents 5

7 Apparatus 5
7.1 Air sampling -- Equipment and consumable supplies 5
7.2 Specimen preparation laboratories 6
7.3 Equipment for analysis 6
7.4 Consumables 6

8 Measuring range 7

9 Limit of detection 7

10 Procedure 7
10.1 General 7
10.2 Sample collection 7
10.3 Deuterated internal standard preparation 8
10.4 Calibration curve preparation 8
10.4.1 Stock solutions 8
10.4.2 Calibration curves 9
10.5 Sample preparation 9
10.5.1 Filter conditioning 9
10.5.2 Total PM2,5 and PM10 10
10.5.3 Filter preparation 10
10.5.4 Internal standard addition 10
10.6 Sample pyrolysis 10
10.7 Sample measurement 10

11 Analysis 11
11.1 General 11
11.2 Total PM2,5 or PM10 concentration 11
11.3 TRWP detection limit 11
11.4 Quantity of tyre polymer in the sample 11
11.5 Air concentration of TRWP 11
11.6 Mass concentration of TRWP 12

12 Performance characteristics 12
12.1 General 12
12.2 Specific performance characteristics 12
12.3 Method detection limit 12

13 Test report 12

Annex A (informative) Recipe for calibration curves and stock solutions 14

Annex B (informative) Curie-point pyrolyser 16

Annex C (informative) Representative calibration curves and pyrograms 17

Annex D (normative) Calculation of TRWP detection limits 24

Annex E (normative) Calculation of results using dimer markers 26

Bibliography 28