

ISO/TS 20593:2017-06 (E)

Ambient air - Determination of the mass concentration of tire and road wear particles (TRWP) - Pyrolysis-GC-MS method

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	3
4.1 Symbols of units (see also ISO 4226)	3
4.2 Abbreviated terms	3
5 Principle	4
6 Reagents	5
7 Apparatus	5
7.1 Air sampling -- Equipment and consumable supplies	5
7.2 Specimen preparation laboratories	6
7.3 Equipment for analysis	6
7.4 Consumables	6
8 Measuring range	7
9 Limit of detection	7
10 Procedure	7
10.1 General	7
10.2 Sample collection	7
10.3 Deuterated internal standard preparation	8
10.4 Calibration curve preparation	8
10.4.1 Stock solutions	8
10.4.2 Calibration curves	9
10.5 Sample preparation	9
10.5.1 Filter conditioning	9
10.5.2 Total PM_{2,5} and PM₁₀	10
10.5.3 Filter preparation	10
10.5.4 Internal standard addition	10
10.6 Sample pyrolysis	10
10.7 Sample measurement	10
11 Analysis	11
11.1 General	11
11.2 Total PM_{2,5} or PM₁₀ concentration	11
11.3 TRWP detection limit	11
11.4 Quantity of tyre polymer in the sample	11
11.5 Air concentration of TRWP	11
11.6 Mass concentration of TRWP	12

12	Performance characteristics	12
12.1	General	12
12.2	Specific performance characteristics	12
12.3	Method detection limit	12
13	Test report	12
Annex A (informative) Recipe for calibration curves and stock solutions		14
Annex B (informative) Curie-point pyrolyser		16
Annex C (informative) Representative calibration curves and pyograms		17
Annex D (normative) Calculation of TRWP detection limits		24
Annex E (normative) Calculation of results using dimer markers		26
Bibliography		28