ISO 28902-2:2017-07 (E)

Air quality - Environmental meteorology - Part 2: Ground-based remote sensing of wind by heterodyne pulsed Doppler lid ar

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Fundamentals of heterodyne pulsed Doppler lidar 4
4.1 Overview 4
4.2 Heterodyne detection 5
4.3 Spectral analysis 7
4.4 Target variables 10
4.5 Sources of noise and uncertainties 10
4.5.1 Local oscillator shot noise 10
4.5.2 Detector noise 11
4.5.3 Relative intensity noise (RIN) 11
4.5.4 Speckles 11
4.5.5 Laser frequency 11
4.6 Range assignment 11
4.7 Known limitations 11

5 Systemspecificationsandtests 12
5.1 System specifications 12
5.1.1 Transmitter characteristics 12
5.1.2 Transmitter/receiver characteristics 13
5.1.3 Signal sampling parameters 13
5.1.4 Pointing system characteristics 14
5.2 Relationship between system characteristics and performance 15
5.2.1 Figure of merit 15
5.2.2 Time-bandwidth trade-offs 16
5.3 Precision and availability of measurements 17
5.3.1 Radial velocity measurement accuracy 17
5.3.2 Data availability 17
5.3.3 Maximum operational range 17
5.4 Testing procedures 18
5.4.1 General 18
5.4.2 Radial velocity measurement validation 18
5.4.3 Assessment of accuracy by intercomparison with other instrumentation 20
5.4.4 Maximum operational range validation 21

6 Measurement planning and installation instructions 23
6.1 Site requirements 23
6.2 Limiting conditions for general operation 23
6.3 Maintenance and operational test 24
6.3.1 General 24
6.3.2 Maintenance 24
6.3.3 Operational test 24
6.3.4 Uncertainty 24

Annex A (informative) Continuous-wave Doppler wind lidar 26

Annex B (informative) Retrieval of the wind vector 27

Annex C (informative) Applications 32

Annex D (informative) Typical application ranges and corresponding requirements 36

Bibliography 38