

ISO 28902-2:2017-07 (E)

Air quality - Environmental meteorology - Part 2: Ground-based remote sensing of wind by heterodyne pulsed Doppler lidar

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Fundamentals of heterodyne pulsed Doppler lidar	4
4.1	Overview	4
4.2	Heterodyne detection	5
4.3	Spectral analysis	7
4.4	Target variables	10
4.5	Sources of noise and uncertainties	10
4.5.1	Local oscillator shot noise	10
4.5.2	Detector noise	11
4.5.3	Relative intensity noise (RIN)	11
4.5.4	Speckles	11
4.5.5	Laser frequency	11
4.6	Range assignment	11
4.7	Known limitations	11
5	System specifications and tests	12
5.1	System specifications	12
5.1.1	Transmitter characteristics	12
5.1.2	Transmitter/receiver characteristics	13
5.1.3	Signal sampling parameters	13
5.1.4	Pointing system characteristics	14
5.2	Relationship between system characteristics and performance	15
5.2.1	Figure of merit	15
5.2.2	Time-bandwidth trade-offs	16
5.3	Precision and availability of measurements	17
5.3.1	Radial velocity measurement accuracy	17
5.3.2	Data availability	17
5.3.3	Maximum operational range	17
5.4	Testing procedures	18
5.4.1	General	18
5.4.2	Radial velocity measurement validation	18
5.4.3	Assessment of accuracy by intercomparison with other instrumentation	20
5.4.4	Maximum operational range validation	21
6	Measurement planning and installation instructions	23
6.1	Site requirements	23
6.2	Limiting conditions for general operation	23
6.3	Maintenance and operational test	24
6.3.1	General	24
6.3.2	Maintenance	24
6.3.3	Operational test	24
6.3.4	Uncertainty	24

Annex A (informative) Continuous-wave Doppler wind lidar	26
Annex B (informative) Retrieval of the wind vector	27
Annex C (informative) Applications	32
Annex D (informative) Typical application ranges and corresponding requirements	36
Bibliography	38