

# ISO 9096:2017-09 (E)

## Stationary source emissions - Manual determination of mass concentration of particulate matter

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Principle .....	4
4.1	General .....	4
4.2	Interferences .....	5
5	Sampling plane and sampling points .....	5
5.1	General .....	5
5.2	Sampling plane .....	6
5.3	Requirements for sampling points .....	6
5.4	Minimum number and location of sampling points .....	6
5.5	Access ports .....	7
5.6	Sampling time .....	7
6	Apparatus and materials .....	8
6.1	Gas velocity, temperature, pressure, and gas composition measurement devices .....	8
6.2	Sampling apparatus .....	8
6.3	Material for particulate matter recovery .....	14
6.4	Apparatus for conditioning and weighing .....	14
7	Sampling and weighing procedures .....	15
7.1	General aspects .....	15
7.2	Weighing procedure .....	16
7.2.1	Parts to be weighed .....	16
7.2.2	Pre-sampling treatment of weighed parts .....	16
7.2.3	Weighing .....	16
7.2.4	Post-sampling treatment of weighed parts .....	17
7.2.5	Post-sampling treatment of the rinsing solutions .....	17
7.3	Sampling .....	18
7.3.1	Preparation .....	18
7.3.2	Pre-measurements .....	18
7.3.3	Calculating the nozzle diameter .....	18
7.3.4	Overall blank .....	20
7.3.5	Sampling procedure .....	20
7.3.6	Recovery of deposits upstream of the filter .....	21
7.4	Validation of results .....	21
7.4.1	Parameters depending on the stationary source .....	21
7.4.2	Leak check .....	21
7.4.3	Isokinetic flowrate .....	22
7.4.4	Deposits of dust on non-weighed parts upstream of the filter .....	22
7.4.5	Validation of sample collection .....	22
7.4.6	Summary of the requirements of this document .....	22

<b>8</b>	<b>Additional aspects .....</b>	<b>22</b>
<b>8.1</b>	<b>Thermal behaviour of particulate matter .....</b>	<b>22</b>
<b>8.2</b>	<b>Particulate deposits upstream of the filter .....</b>	<b>24</b>
<b>8.3</b>	<b>Improvement of the weighing procedure .....</b>	<b>24</b>
<b>9</b>	<b>Calculations .....</b>	<b>25</b>
<b>9.1</b>	<b>Isokinetic flowrate .....</b>	<b>25</b>
<b>9.2</b>	<b>Dust concentration .....</b>	<b>25</b>
<b>9.2.1</b>	<b>General .....</b>	<b>25</b>
<b>9.2.2</b>	<b>Oxygen correction factor .....</b>	<b>26</b>
<b>9.2.3</b>	<b>Carbon dioxide correction factor .....</b>	<b>26</b>
<b>10</b>	<b>Performance characteristics .....</b>	<b>26</b>
<b>10.1</b>	<b>General aspects .....</b>	<b>26</b>
<b>10.2</b>	<b>Experimental data for sampling .....</b>	<b>27</b>
<b>11</b>	<b>Test report .....</b>	<b>27</b>
	<b>Annex A (normative) Proven design of the entry nozzle .....</b>	<b>29</b>
	<b>Annex B (normative) Determination of positions of sampling points in circular and rectangular ducts .....</b>	<b>30</b>
	<b>Annex C (informative) Examples of weighing bias .....</b>	<b>34</b>
	<b>Annex D (informative) Isokinetic sampling conditions .....</b>	<b>36</b>
	<b>Annex E (informative) Summary validation information .....</b>	<b>38</b>
	<b>Annex F (informative) Examples of suitable access ports for sampling equipment .....</b>	<b>41</b>
	<b>Bibliography .....</b>	<b>43</b>