ISO 16000-24:2018 (E)

Indoor air — Part 24: Performance test for evaluating the reduction of volatile organic compound concentrations by sorptive building materials

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Principle

6 Apparatus and materials

7 Test conditions

- 7.1 General
- 7.2 Test conditions to determine concentration reduction performance
- 7.2.1 Temperature and relative humidity
- 7.2.2 Supply air quality and background concentration
- 7.2.3 Mass transfer coefficient
- 7.2.4 Air change rate
- 7.2.5 Supply air concentration
- 7.3 Factors affecting the concentration reduction performance
- 7.3.1 General
- 7.3.2 Temperature and humidity
- 7.3.3 Concentration of target compound(s) in spiked air
- 7.3.4 Interfering gases

8 Verification of test conditions

- 8.1 Monitoring of test conditions
- 8.2 Airtightness of test chamber
- 8.3 Air change rate in test chamber
- 8.4 Efficiency of the internal test chamber air mixing
- 8.5 Recovery

9 Preparation of test chamber

10 Preparation of test specimens

11 Test method

- 11.1 Background concentration and spiked supply air
- 11.2 Placing the test specimen in the test chamber
- 11.3 Time intervals for measurement of chamber concentration
- 11.3.1 Test for concentration reduction performance
- 11.3.2 Test for long-term reduction performance
- 11.3.3 Factors affecting the reduction performance
- 11.4 Air sampling

12 Determination of target compound(s)

13 Expression of results

13.1 Calculation of area-specific reduction rate
13.2 Calculation of equivalent ventilation rate per area
13.3 Calculation of total mass per area of sorption and saturation mass per area

14 Test report

Annex A (normative) Sample tube test for long-term reduction performance

A.1 Principle
A.1.1 General
A.1.2 Target compound reduction by physical sorption
A.1.3 Target compound reduction by chemisorption and/or decomposition reaction
A.2 Apparatus and materials
A.3 Test conditions
A.3.1 Supply air concentration
A.3.2 Temperature and relative humidity
A.4 Test method
A.4.1 Sampling and pretreatment of test specimen
A.4.2 Preparation of sample tubes
A.4.3 Monitoring the concentration of target compound(s) in spiked air
A.4.4 Test for the breakthrough time of target compounds
A.4.5 Expression of results
A.4.5.1 Calculation of sorption capacity
A.4.5.2 Calculation of saturation mass per area

Annex B (normative) System for quality assurance and quality control

B.1 General
B.2 Project description
B.3 Data quality objectives and acceptance criteria
B.4 QA/QC approaches and activities
B.5 QA/QC audits

Page count: 19