

# DIN ISO 16000-23:2019-03 (E)

**Indoor air - Part 23: Performance test for evaluating the reduction of formaldehyde and other carbonyl compounds concentrations by sorptive building materials (ISO 16000-23:2018)**

---

## Contents

|  | Page |
|--|------|
| National foreword .....  | 4    |
| Foreword .....   | 6    |
| Introduction .....   | 7    |
| 1 Scope .....  | 8    |
| 2 Normative references .....   | 8    |
| 3 Terms and definitions .....  | 8    |
| 4 Symbols .....  | 11   |
| 5 Principle .....  | 11   |
| 6 Apparatus and materials .....  | 12   |
| 7 Test conditions .....  | 13   |
| 7.1 General .....  | 13   |
| 7.2 Test conditions to determine concentration reduction performance ..... | 13   |
| 7.2.1 Temperature and relative humidity .....                              | 13   |
| 7.2.2 Supply air quality and background concentration .....                | 13   |
| 7.2.3 Mass transfer coefficient .....                                      | 14   |
| 7.2.4 Air change rate .....  | 14   |
| 7.2.5 Supply air concentration .....                                       | 14   |
| 7.3 Factors affecting the concentration reduction performance .....        | 14   |
| 7.3.1 General .....  | 14   |
| 7.3.2 Temperature and humidity .....                                       | 14   |
| 7.3.3 Concentration of target compound(s) in supply air .....              | 14   |
| 7.3.4 Interfering gases .....  | 15   |
| 8 Verification of test conditions .....                                    | 15   |
| 8.1 Monitoring of test conditions .....                                    | 15   |
| 8.2 Airtightness of test chamber .....                                     | 15   |
| 8.3 Air change rate in test chamber .....                                  | 15   |
| 8.4 Efficiency of the internal test chamber air mixing .....               | 15   |
| 8.5 Recovery .....   | 15   |
| 9 Preparation of test chamber .....  | 16   |
| 10 Preparation of test specimens .....                                     | 16   |
| 11 Test method .....   | 16   |
| 11.1 Background concentration and spiked supply air .....                  | 16   |
| 11.2 Placing the test specimen in the test chamber .....                   | 16   |
| 11.3 Time intervals for measurement of test chamber concentration .....    | 16   |
| 11.3.1 Test for target compound concentration reduction .....              | 16   |
| 11.3.2 Test for long-term reduction performance .....                      | 17   |
| 11.3.3 Factors affecting the reduction performance .....                   | 17   |
| 11.4 Air sampling .....  | 17   |
| 12 Determination of target compound(s) .....                               | 17   |

|   |  |           |
|---|--|-----------|
| <b>13</b>   | <b>Expression of results.....</b>  | <b>17</b> |
| 13.1  | Calculation of area-specific reduction rate.....                                 | 17        |
| 13.2  | Calculation of equivalent ventilation rate per area.....                         | 18        |
| 13.3  | Calculation of total mass per area of sorption and saturation mass per area..... | 18        |
| <b>14</b>   | <b>Test report.....</b>  | <b>18</b> |
| <b>Annex A (normative) Sample tube test for long-term reduction performance .....</b>   |  | <b>20</b> |
| <b>Annex B (normative) System for quality assurance and quality control.....</b>        |  | <b>24</b> |
| <b>Annex C (informative) Example measurements of construction materials.....</b>        |  | <b>26</b> |
| <b>Annex D (informative) Example procedure for long-term reduction performance.....</b> |  | <b>31</b> |
| <b>Bibliography.....</b>  |  | <b>34</b> |