DIN EN 17389:2020-07 (E)

Stationary source emissions - Quality assurance and quality control procedures for automated dust arrestment plant monitors

Contents

Page

European foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Symbols and abbreviations 10
4.1 Symbols 10
4.2 Abbreviations 10

5 Principle 10

6 Selection and installation of a suitable instrument 10
6.1 Selection 10
6.2 Installation 11

7 Configuration of instruments 11
7.1 General 11
7.2 Configuration of filter dust monitors 11
7.2.1 General 11
7.2.2 Service test 11
7.2.3 Parallel measurements with the SRM 12
7.2.4 Data evaluation and calibration function 13
7.2.5 Setting of dust alarm limits 14
7.3 Configuration of a filter leakage monitor 14
7.3.1 General 14
7.3.2 Service test 15
7.3.3 Setting of range and dust alarm limits 15

8 Ongoing quality assurance during operation 15

9 Annual surveillance test 16

Annex A (informative) Extension of the calibration range by changing the dust concentration 17

A.1 General 17
A.2 Changing plant load 17
A.3 Changing operation of dust arrestment plant 17
A.4 Injection of dust 17

Annex B (informative) Explanation of bag filter operation, bag cleaning and filter leakage monitoring 19

Figure B.1 -- Dust pulses associated with bag cleaning superimposed on the baseline emission - mass concentration c as a function of time t (5 min intervals) 19

Figure B.2 -- Changes in dust emissions associated with filter leak - mass concentration c as a function of time in days d of a calendar month 20

Bibliography 21