

DIN EN 17389:2020-07 (E)

Stationary source emissions - Quality assurance and quality control procedures for automated dust arrestment plant monitors

Contents		Page
European foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and abbreviations	10
4.1	Symbols	10
4.2	Abbreviations	10
5	Principle	10
6	Selection and installation of a suitable instrument	10
6.1	Selection	10
6.2	Installation	11
7	Configuration of instruments	11
7.1	General	11
7.2	Configuration of filter dust monitors	11
7.2.1	General	11
7.2.2	Service test	11
7.2.3	Parallel measurements with the SRM	12
7.2.4	Data evaluation and calibration function	13
7.2.5	Setting of dust alarm limits	14
7.3	Configuration of a filter leakage monitor	14
7.3.1	General	14
7.3.2	Service test	15
7.3.3	Setting of range and dust alarm limits	15
8	Ongoing quality assurance during operation	15
9	Annual surveillance test	16
Annex A (informative) Extension of the calibration range by changing the dust concentration		17
A.1	General	17
A.2	Changing plant load	17
A.3	Changing operation of dust arrestment plant	17
A.4	Injection of dust	17
Annex B (informative) Explanation of bag filter operation, bag cleaning and filter leakage monitoring		19
Figure B.1 -- Dust pulses associated with bag cleaning superimposed on the baseline emission - mass concentration c as a function of time t (5 min intervals)		19
Figure B.2 -- Changes in dust emissions associated with filter leak - mass concentration c as a function of time in days d of a calendar month		20
Bibliography		21