ISO 12219-10:2021 (E)

Interior air of road vehicles — Part 10: Whole vehicle test chamber — Specification and methods for the determination of volatile organic compounds in cabin interiors — Trucks and buses

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Apparatus and materials

4.1 General
4.2 Heating radiator
4.3 Sampling trains
4.3.1 Sampling in the test vehicle
4.3.2 Sampling in the whole vehicle test chamber
4.3.3 Sampling line
4.4 Analytical equipment and materials
4.5 Test vehicle

5 Principle

6 Requirements of the whole vehicle test chamber, test vehicle and measurement procedures

6.1 Requirements for the whole vehicle test chamber
6.2 Requirements for the test vehicle
6.3 Requirements for VOC and carbonyl compound air sampling and measurement methods
6.4 Field blank measurement

7 Standard test procedure

7.1 General
7.2 Pre-arrangements and preconditioning of the whole vehicle test chamber and the vehicle performing field blanks
7.2.1 Pre-arrangements
7.2.2 Preconditioning of the whole vehicle test chamber
7.2.3 Preconditioning of the test vehicle
7.2.4 Field blanks
7.3 Detailed description of the test procedure
7.3.1 Ambient mode
7.3.1.1 Preconditioning time 0 (see scheme in Figure 3)
7.3.1.2 Time: 1,00 h
7.3.1.3 Time 8,50 h
7.3.2 Parking mode
7.3.2.1 Time 9,00 h
7.3.2.2 Time 12,50 h
7.3.3 Driving mode
7.3.3.1 Time 13,00 h
7.3.3.2 Time 13,5 h for trucks, 15 h for buses

8 Calculation, presentation of results, and precision and uncertainty

9 Performance characteristics

10 Quality assurance

Annex A (informative) Whole vehicle test chamber and the ambient mode chamber condition

Annex B (informative) VOC concentration distribution in the bus cabin

Annex C (informative) Temperature measuring points for parking mode

Annex D (informative) Test report

Annex E (informative) Very volatile organic compounds, volatile organic compounds and semi-volatile organic compounds

Page count: 19