DIN EN 13725:2022-06 (E)

Stationary source emissions - Determination of odour concentration by dynamic olfactometry and odour emission rate

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 6

3 Terms and definitions 6
3.1 Terms and definitions for olfactometry 7
3.2 Terms and definitions for sampling 13
3.3 Terms and definitions for metrology and statistics 16

4 Symbols and abbreviated terms 22

5 Principle of method 24
5.1 Odour measurement: odorant gas sampling and odour analysis 24
5.2 Odorant gas sampling 24
5.3 Determination of odour concentration 25

6 Apparatus and materials 28
6.1 General properties of materials 28
6.2 Sampling equipment 28
6.3 Sample container 29
6.4 Gases 30
6.5 Dilution apparatus 31
6.6 Environment for observations by assessors 33
6.7 Panel 34

7 Performance characteristics and criteria 36
7.1 General 36
7.2 Accuracy - statistical model 37
7.3 Overall sensory quality requirements 37
7.4 Quality requirements for dilution apparatus 40

8 Measurement objective and measurement plan 44
8.1 General 44
8.2 Preliminary investigation 44
8.3 Measurement plan 44

9 Measurement procedure 45
9.1 Sampling 45
9.2 Sampling of a point source 50
9.3 Sampling of area sources 50
9.4 Olfactometric analysis 55
9.5 Occupational safety for sampling personnel, assessors and olfactometry operators 57
9.6 Validation and calculation of results 60

10 Quality assurance and quality control procedures 62
10.1 Field blank 62
10.2 Measurement uncertainty 63
10.3 Determination of the limit of detection (LoD) and the limit of quantification (LoQ) 69

11 Measurement records and report 71
11.1 General 71
11.2 Records and reporting for emission sampling 71
11.3 Records and reporting for odour concentration measurement 72

Annex A (informative) Physiological principles 74

Annex B (informative) Example of calculation of instrumental accuracy and instability 78

Annex C (informative) Example of calculation of odour measurements within one laboratory 81

Annex D (informative) Example of calculations for panel selection 83

Annex E (informative) Example of the calculation of the odour concentration from a set of panel member responses 85

Annex F (informative) Example of the calculation used to determine the number of odour concentration measurements required to achieve a defined precision 89

Annex G (informative) Example of the calculation used to determine the number of odour concentration measurements required to determine a difference between two means 91

Annex H (informative) Example of the calculation of the odour flow rate (standard conditions) for a wet emission 94

Annex I (informative) Example of the calculation of an SROM value for a new defined odorant from an EROM comparison 95

Annex J (informative) Example of the calculation of measurement uncertainty 105

Annex K (informative) Dynamic dilution apparatus for sampling 113

Annex L (informative) Considerations for the interpretation of the odour concentration concept for air quality management 116

Annex M (informative) Sampling of passive area sources 117

Annex N (informative) Significant technical changes 119

Bibliography 123