

DIN EN 14662-1:2024-05 (E)

Ambient air quality - Standard method for measurement of benzene concentrations - Part 1: Pumped sampling followed by thermal desorption and gas chromatography

Contents		Page
European foreword		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Method description	11
4.1	Principle	11
4.2	Reagents and materials	11
4.3	Apparatus	13
4.4	Sampler conditioning and blank profiling	17
4.5	Setting of sampling flow rate	18
4.6	Sampling	18
5	Air inlet/manifold sampling equipment	19
5.1	General	19
5.2	Sampling location	19
5.3	Sample delivery	20
6	Type testing	21
6.1	General	21
6.2	Relevant performance characteristics and performance criteria	21
6.3	Type testing programme	24
7	Field operations and ongoing quality control	31
7.1	General	31
7.2	Frequency of calibrations, checks and maintenance	31
7.3	Maintenance of the sampling device	32
7.4	Checks of sampling device sensors	32
7.5	Calibration of sampling device sensors	32
7.6	Checks of the sampling system flow rate	32
7.7	Calibration of the sampling device flow rate	33
7.8	Leak check of the sampling system	33
7.9	Evaluation of sample losses in the sampling device	33
8	Determination of measurement uncertainty	33
8.1	General	33
8.2	Parameters contributing to measurement uncertainty	34
9	Report	35
10	Recommendations for use	35
Annex A (informative) Sorbent selection and characteristics		36
Annex B (informative) Analysis of exposed samples		38
B.1	Safety precautions	38
B.2	Thermal desorption	38

B.3	Determination of desorption efficiency	39
B.4	Calibration	39
B.5	Determination of sample concentration	40
B.6	Calculation of mass concentration of benzene	40
Annex C (informative) Determination of breakthrough volume from gas standards		41
C.1	Reagents	41
C.2	Apparatus	41
C.3	Determination	41
C.4	Calculations	42
Annex D (informative) Determination of breakthrough volumes from extrapolated retention volumes		43
D.1	Apparatus	43
D.2	Reagents	43
D.3	Determination	43
D.4	Expression of results	43
Annex E (informative) Assessment of performance indicators and uncertainty contributions		44
E.1	General	44
E.2	Sample volume	44
E.2.1	General	44
E.2.2	Sample flow calibration and measurement	45
E.2.3	Sampling time	46
E.2.4	Conversion of sampling volume to STP	46
E.2.4.1	Mass-flow controlled sampling devices	46
E.2.4.2	Volume-controlled sampling devices	47
E.3	Desorption efficiency and analytical repeatability	48
E.3.1	Introduction	48
E.3.2	Desorption efficiency	48
E.3.3	Analytical repeatability	48
E.4	Mass of benzene sampled	49
E.4.1	General	49
E.4.2	Sampling efficiency	49
E.4.3	Sample stability	49
E.4.4	Corrections to the measured mass of benzene	50
E.4.4.1	General	50
E.4.4.2	Calibration standards	50
E.4.4.3	Lack-of-fit of calibration function	50
E.4.4.4	Response drift between calibrations	51
E.4.4.5	Selectivity	51
E.4.5	Combined uncertainty in the measured mass of benzene	52
E.4.6	Combined uncertainty in the sampled mass of benzene	53
E.5	Mass of benzene in sample blank	53
E.6	Combined uncertainty in benzene concentration	53
E.7	Expanded uncertainty	54
E.8	Uncertainty from performance requirements	54
E.8.1	General	54
E.8.2	Analyte Ingress from air being sampled	54
E.8.3	Analyte Ingress from Surrounding Air	56
E.8.4	Loss of Retained Analyte	56
E.9	Between-laboratory uncertainty	59
E.10	Example for uncertainty budget calculation	60
Annex F (informative) Reproducibility, validation and comparison exercises		62
Annex G (informative) Performance characteristics		63
G.1	Prior art	63

G.2	Results of inter-laboratory comparisons	64
Annex H (informative)	Sampling equipment	66
Annex I (informative)	Significant technical changes	70
Bibliography		71