

ISO 16000-44:2023-12 (E)

Indoor air - Part 44: Test method for measuring perceived indoor air quality for use in testing the performance of gas phase air cleaners

| Contents | Page |
|--------------------------------------------------------------------------------------------------|-------------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Principle | 2 |
| 5 Apparatus, materials and sensory panel | 3 |
| 6 Test conditions | 4 |
| 6.1 General..... | 4 |
| 6.2 Temperature and relative humidity..... | 5 |
| 6.3 Supply air quality and background concentration..... | 5 |
| 6.4 Air change rate..... | 5 |
| 6.5 Panel members..... | 5 |
| 6.6 Anterior space condition..... | 5 |
| 7 Preparation | 6 |
| 7.1 Preparation of the odour emission source(s)..... | 6 |
| 7.2 Preparation of air cleaner(s)..... | 6 |
| 8 Test method | 6 |
| 8.1 Test chamber method..... | 6 |
| 8.1.1 General..... | 6 |
| 8.1.2 Step 1: Measuring the perceived air quality without operating air cleaner(s)..... | 6 |
| 8.1.3 Step 2: Measuring the perceived air quality with operating air cleaner(s)..... | 7 |
| 8.1.4 Determination of perceived air quality..... | 7 |
| 8.1.5 Instructions..... | 9 |
| 9 Efficiency | 9 |
| 10 Test report | 9 |
| Annex A (informative) System for quality assurance and quality control | 11 |
| Annex B (informative) Examples of Test conditions for test chamber and air purifier | 13 |
| Annex C (normative) Test conditions for whole-body exposure in test chamber | 14 |
| Bibliography | 16 |