

ISO 16000-9:2024-03 (E)

Indoor air - Part 9: Determination of the emission of volatile organic compounds from samples of building products and furnishing - Emission test chamber method

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Symbols and abbreviated terms		3
4.1 Symbols		3
4.2 Abbreviated terms		4
5 Principle		4
6 Emission test chamber system		4
6.1 General		4
6.2 Emission test chamber materials		4
6.3 Air supply and mixing facilities		4
6.4 Air tightness		5
6.5 Air sampling devices		5
6.6 Recovery and sink effects		5
7 Apparatus		5
8 Test conditions		6
8.1 Temperature and relative air humidity		6
8.2 Supply air quality and background concentration		6
8.3 Air velocity		6
8.4 Area specific air flow rate and air change rate		6
9 Verification of the test conditions		7
9.1 General		7
9.2 Temperature and relative air humidity control systems		7
9.3 Air change rate in the emission test chamber		7
9.4 Emission test chamber air tightness		7
9.5 Air velocity in the emission test chamber		7
9.6 Efficiency of the internal emission test chamber air mixing		7
10 Test specimens		8
11 Emission test chamber preparation		8
12 Test method		8
12.1 Background concentrations		8
12.2 Test specimen location in the emission test chamber		8
12.3 Time for measurements of test chamber air concentration		8
13 Calculation of area specific emission rates and expression of results		9
14 Performance characteristics		9
15 Test report		9
Annex A (normative) System for quality assurance and quality control		11
Annex B (informative) Examples of loading factors for a model room		13
Annex C (informative) General description of an emission test chamber		14
Annex D (informative) Determination of the emission rates of seams and cut edges		15
Bibliography		16