

# DIN EN 16976:2024-09 (E)

## Ambient air - Determination of the particle number concentration of atmospheric aerosol

---

| <b>Contents</b>         |  | <b>Page</b> |
|-------------------------|--|-------------|
| European foreword ..... |  | 5           |
| Introduction .....      |  | 7           |
| <b>1</b>                | <b>Scope .....</b>   | <b>8</b>    |
| <b>2</b>                | <b>Normative references .....</b>  | <b>8</b>    |
| <b>3</b>                | <b>Terms and definitions .....</b>   | <b>8</b>    |
| <b>3.1</b>              | <b>Aerosol properties .....</b>  | <b>8</b>    |
| <b>3.2</b>              | <b>Instrument performance .....</b>  | <b>9</b>    |
| <b>3.3</b>              | <b>Flow rates .....</b>  | <b>9</b>    |
| <b>4</b>                | <b>Atmospheric aerosol .....</b>   | <b>10</b>   |
| <b>5</b>                | <b>Description of the method .....</b>   | <b>10</b>   |
| <b>5.1</b>              | <b>Sampling and conditioning .....</b>   | <b>10</b>   |
| <b>5.1.1</b>            | <b>Sampling .....</b>  | <b>10</b>   |
| <b>5.1.2</b>            | <b>Drying .....</b>  | <b>12</b>   |
| <b>5.1.3</b>            | <b>Dilution .....</b>  | <b>12</b>   |
| <b>5.2</b>              | <b>Determination of the number concentration with a CPC .....</b>                              | <b>13</b>   |
| <b>5.2.1</b>            | <b>Condensation growth .....</b>   | <b>13</b>   |
| <b>5.2.2</b>            | <b>Optical detection .....</b>   | <b>15</b>   |
| <b>6</b>                | <b>CPC performance criteria and test procedures .....</b>                                      | <b>15</b>   |
| <b>6.1</b>              | <b>General .....</b>   | <b>15</b>   |
| <b>6.2</b>              | <b>General requirements for the CPC .....</b>  | <b>15</b>   |
| <b>6.3</b>              | <b>Test conditions .....</b>   | <b>16</b>   |
| <b>6.4</b>              | <b>Performance characteristics and criteria .....</b>  | <b>17</b>   |
| <b>6.5</b>              | <b>Test procedures .....</b>   | <b>18</b>   |
| <b>6.5.1</b>            | <b>Calibrated flow rate .....</b>  | <b>18</b>   |
| <b>6.5.2</b>            | <b>Number concentration measurement range .....</b>  | <b>18</b>   |
| <b>6.5.3</b>            | <b>Number concentration detection limit .....</b>  | <b>18</b>   |
| <b>6.5.4</b>            | <b>Calibration factor .....</b>  | <b>18</b>   |
| <b>6.5.5</b>            | <b>Instrument-specific assessment of linearity and slope of response .....</b>                 | <b>18</b>   |
| <b>6.5.6</b>            | <b>Detection efficiency curve at low particle size .....</b>                                   | <b>19</b>   |
| <b>6.5.7</b>            | <b>Upper particle size detection limit .....</b>   | <b>19</b>   |
| <b>6.5.8</b>            | <b>Zero count rate .....</b>   | <b>19</b>   |
| <b>6.5.9</b>            | <b>Response time .....</b>   | <b>19</b>   |
| <b>6.5.10</b>           | <b>Dependence of flow rate on supply voltage .....</b>   | <b>20</b>   |
| <b>6.5.11</b>           | <b>Measurement uncertainty of temperature and pressure sensor calibration .....</b>            | <b>20</b>   |
| <b>6.5.12</b>           | <b>Effect of failure of mains voltage .....</b>  | <b>20</b>   |
| <b>7</b>                | <b>Performance criteria and test procedures for the sampling and conditioning system .....</b> | <b>20</b>   |
| <b>7.1</b>              | <b>General requirements .....</b>  | <b>20</b>   |
| <b>7.2</b>              | <b>Performance characteristics and criteria .....</b>  | <b>20</b>   |
| <b>7.3</b>              | <b>Diffusion losses .....</b>  | <b>21</b>   |
| <b>7.4</b>              | <b>Relative humidity .....</b>   | <b>21</b>   |
| <b>7.5</b>              | <b>Dilution .....</b>  | <b>21</b>   |
| <b>7.5.1</b>            | <b>Dilution factor .....</b>   | <b>21</b>   |
| <b>7.5.2</b>            | <b>General criteria for dilution systems .....</b>   | <b>22</b>   |

|        |  |    |
|--------|--|----|
| 7.6    | Primary sampling flow .....  | 22 |
| 8      | Measurement procedure .....  | 22 |
| 8.1    | Measurement planning .....   | 22 |
| 8.2    | Environmental operating conditions .....   | 22 |
| 8.3    | Initial installation .....   | 23 |
| 8.4    | Initial checks on site .....   | 23 |
| 8.5    | Data processing and reporting .....  | 23 |
| 9      | Quality control, quality assurance and measurement uncertainty .....                             | 24 |
| 9.1    | General .....  | 24 |
| 9.2    | Frequency of calibrations, checks and maintenance .....  | 24 |
| 9.2.1  | General .....  | 24 |
| 9.2.2  | Full maintenance of CPC .....  | 25 |
| 9.2.3  | Calibration of linearity .....   | 25 |
| 9.2.4  | Zero check .....   | 25 |
| 9.2.5  | Number concentration check .....   | 25 |
| 9.2.6  | Actual flow rate check .....   | 25 |
| 9.2.7  | Temperature and pressure sensor calibration .....  | 26 |
| 9.2.8  | CPC internal diagnostics .....   | 26 |
| 9.2.9  | Sample system maintenance .....  | 26 |
| 9.2.10 | Relative humidity sensor .....   | 26 |
| 9.2.11 | Dilution factor (where applicable) .....   | 26 |
| 9.2.12 | Leak check .....   | 26 |
| 9.3    | Measurement uncertainty .....  | 26 |
| 9.3.1  | General .....  | 26 |
| 9.3.2  | CPC plateau detection efficiency .....   | 27 |
| 9.3.3  | CPC detection efficiency drift .....   | 27 |
| 9.3.4  | Flow determination .....   | 28 |
| 9.3.5  | Correction to standard temperature and pressure .....  | 28 |
| 9.3.6  | Diffusion losses in the sampling system .....  | 28 |
| 9.3.7  | Dilution factor (where applicable) .....   | 28 |
| 9.3.8  | Calculation of overall uncertainty .....   | 29 |
|        | Annex A (normative) Determination of diffusion losses in sampling lines .....                    | 30 |
|        | Annex B (informative) Example of the calculation of diffusion losses in a sampling system 32 B.1 |    |
|        | Description of the sampling system .....   | 32 |
| B.2    | Air properties and diffusion coefficient .....   | 33 |
| B.3    | Losses in the primary sampling tube .....  | 33 |
| B.4    | Losses in the secondary sampling tube and the dryer .....  | 34 |
| B.5    | Overall sampling losses .....  | 34 |
|        | Annex C (informative) Uncertainty calculation (example) .....                                    | 35 |
| C.1    | General .....  | 35 |
| C.2    | CPC plateau detection efficiency .....   | 35 |
| C.3    | CPC detection efficiency drift .....   | 35 |
| C.4    | Flow determination .....   | 35 |
| C.5    | Correction to standard temperature and pressure .....  | 35 |
| C.6    | Sampling losses due to diffusion to walls .....  | 35 |
| C.7    | Dilution factor (where applicable) .....   | 36 |
| C.8    | Calculation of overall uncertainty .....   | 36 |
|        | Annex D (informative) Atmospheric aerosols .....   | 37 |
| D.1    | General .....  | 37 |
| D.2    | Examples of measurements .....   | 37 |
|        | Annex E (informative) Dilution systems .....   | 40 |

|  |   |           |
|--|---|-----------|
| <b>E.1</b>   | <b>Background</b> .....   | <b>40</b> |
| <b>E.2</b>   | <b>Operation principles of dilution systems</b> .....                                 | <b>40</b> |
| <b>E.3</b>   | <b>Design example of a dilution system for drying the primary sampling flow</b> ..... | <b>42</b> |
| <b>E.4</b>   | <b>Operating parameters of a dilution system</b> .....                                | <b>43</b> |
| <b>E.5</b>   | <b>Example for the calculation of the uncertainty of the dilution factor</b> .....    | <b>46</b> |
| <b>Annex F (informative) Laminar flow</b> .....  |   | <b>48</b> |
| <b>Annex G (informative) Coincidence correction</b> .....                                  |   | <b>49</b> |
| <b>Annex H (informative) Results of an experimental comparison of different CPCs</b> ..... |   | <b>51</b> |
| <b>Bibliography</b> .....  |   | <b>56</b> |