ISO 12219-12:2025-05 (E)

Interior air of road vehicles - Part 12: Test methods for the determination of fogging characteristics of trim materials made from polyvinyl chloride (PVC) or polyurethane in the interior of automobiles

Contents

Page

Foreword ... **iv**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Principle ... **1**

5 Apparatus and materials ... **2**

6 Sample preparation ... **5**

7 Conditioning ... **6**

8 Procedure ... **6**

8.1 Cleaning ... 6

8.1.1 General ... 6

8.1.2 Cleaning with a dishwasher ... 6

8.1.3 Manual cleaning ... 6

8.1.4 Polishing of glass surface ... 6

8.2 Reference tests ... 6

8.3 Placement of test specimens ... 7

8.4 Measurements prior to the fogging test ... 7

8.5 Fogging test ... 7

8.5.1 Set-up ... 7

8.5.2 Determination of the fogging value, F ... 8

8.5.3 Determination of the mass of condensable constituents, G ... 8

9 Expression of results ... **9**

9.1 Fogging value ... 9

9.2 Mass of condensable constituents ... 9

10 Test report ... **9**

Annex A (informative) **Comparison of air chamber and oil bath test results** ... **11**

Annex B (informative) **Confirmation of fogging test bath accuracy by DIDP** ... **13**

Annex C (informative) **Effect of polishing glass plate surface** ... **14**

Bibliography ... **16**