

DIN EN 15714-2:2010-02 (E)

Industrial valves - Actuators - Part 2: Electric actuators for industrial valves - Basic requirements

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Classification/Designation | 5 |
| 3.1 | General | 5 |
| 3.2 | Type: Part-turn, multi-turn or linear | 5 |
| 3.3 | Actuator duty classification | 6 |
| 3.3.1 | General | 6 |
| 3.3.2 | Class A: On-off | 6 |
| 3.3.3 | Class B: Inching/positioning | 6 |
| 3.3.4 | Class C: Modulating | 6 |
| 3.3.5 | Class D: Continuous modulating | 6 |
| 3.4 | Action on loss of external electric power | 6 |
| 3.4.1 | Standard action | 6 |
| 3.4.2 | Fail safe action | 6 |
| 4 | Design requirements | 6 |
| 4.1 | Endurance | 6 |
| 4.1.1 | General | 6 |
| 4.1.2 | Part turn actuators | 7 |
| 4.1.3 | Multi-turn actuators | 7 |
| 4.1.4 | Linear actuators | 8 |
| 4.2 | Environmental conditions | 8 |
| 4.2.1 | General | 8 |
| 4.2.2 | Ambient temperature and humidity | 8 |
| 4.2.3 | Altitude | 8 |
| 4.2.4 | Enclosure protection | 8 |
| 4.2.5 | Hazardous areas | 8 |
| 4.2.6 | External corrosion protection | 9 |
| 4.2.7 | Vibrations, shock and seismic conditions | 9 |
| 4.3 | Actuator attachment | 9 |
| 4.3.1 | Part-turn actuators | 9 |
| 4.3.2 | Multi-turn actuators | 10 |
| 4.3.3 | Linear actuators | 10 |
| 4.4 | Standard closing direction | 11 |
| 4.5 | Fail safe direction | 11 |
| 4.6 | Electrical connections -- cable entries | 12 |
| 4.7 | Performance | 12 |
| 4.7.1 | Power supply tolerances | 12 |
| 4.7.2 | Actuator duty performances | 12 |
| 4.7.3 | Operating time and speed | 14 |
| 4.8 | Basic requirements | 14 |
| 4.8.1 | Motors | 14 |
| 4.8.2 | Gearing and lubrication | 14 |
| 4.8.3 | Manual operation | 15 |
| 4.8.4 | Travel limitation | 15 |
| 4.8.5 | Torque/Thrust limitation | 15 |
| 4.8.6 | End stop adjustment for part-turn and linear actuators | 15 |

| | | |
|-------|--|----|
| 4.8.7 | Local position indication | 15 |
| 10 | 10 5.1 General | 16 |
| 5.2 | Anti-condensation heater | 16 |
| 5.3 | Local position indication (for multi-turn or linear actuators) | 16 |
| 5.4 | Position transmitter | 16 |
| 5.5 | Actuator running transmitter | 16 |
| 5.6 | Additional position and/or torque signalling | 16 |
| 5.7 | Local control station | 16 |
| 5.8 | Actuator electrical controls | 16 |
| 5.8.1 | General | 16 |
| 5.8.2 | Positioner | 17 |
| 5.8.3 | Controller | 17 |
| 5.8.4 | Speed Control | 17 |
| 5.8.5 | Field Bus system interface | 17 |
| 5.8.6 | Torque transmitter (analogue or digital) | 17 |
| 5.8.7 | Actuator performance data logger | 17 |
| 6 | Conformity assessment | 17 |
| 6.1 | General | 17 |
| 6.2 | Type tests | 18 |
| 6.3 | Control of production process and quality system | 18 |
| 7 | Marking | 19 |
| 8 | Documentation | 20 |
| | Annex A (normative) Endurance test procedure | 21 |
| A.1 | General | 21 |
| A.2 | Test equipment | 21 |
| A.3 | Test conditions | 21 |
| A.4 | Test procedure | 21 |
| A.5 | Acceptance criteria | 21 |
| | Annex B (informative) Actuator selection guidelines | 22 |
| B.1 | General | 22 |
| B.2 | Selection parameters | 22 |
| B.2.1 | General | 22 |
| B.2.2 | Valve Questions | 22 |
| B.2.3 | Actuator Questions | 23 |
| B.3 | Ancillary Questions | 23 |
| B.4 | Environmental conditions (as indicated in 4.2) | 23 |
| B.5 | Actuator selection | 23 |
| | Bibliography | 24 |
| 5 | Optional equipment | 16 |