

DIN EN 15714-3:2010-02 (E)

Industrial valves - Actuators - Part 3: Pneumatic part-turn actuators for industrial valves - Basic requirements

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Classification/Designation	5
3.1	General	5
3.2	Action	5
3.3	Actuator attachment	5
3.4	Performance data	6
3.4.1	Output torques	6
3.4.2	Minimum moving pressure	6
3.4.3	Operating time	6
3.4.4	Air volume	6
3.4.5	Motive energy	6
4	Design requirements	6
4.1	Endurance of part-turn actuators	6
4.2	Leakage	7
4.3	Angle for part-turn actuators	7
4.4	Environmental conditions	7
4.4.1	Ambient temperature	7
4.4.2	Enclosure protection	8
4.4.3	Corrosion protection	8
4.5	Basic design	8
4.5.1	Safety requirements	8
4.5.2	Part-turn actuator attachment	9
4.5.3	Pressure connections and pilot valves interface	9
4.5.4	Fail safe direction for spring return actuators	11
4.5.5	Mechanical safety factors	11
4.5.6	Position indication	11
4.6	Optional equipment	11
4.6.1	Ancillaries	11
4.6.2	Manual operation	13
4.6.3	End stop adjustment for part-turn actuators	14
5	Conformity assessment	14
5.1	General	14
5.2	Type tests	14
5.3	Control of production process and quality system	14
6	Marking	15
6.1	General requirements on marking	15
7	Part-turn actuator selection guidelines	16
8	Documentation	16
Annex A (normative)	Endurance test procedure	17

A.1	General	17
A.2	Test equipment	17
A.3	Test conditions	17
A.4	Test procedure	17
A.5	Acceptance criteria	17
Annex B (informative) Actuator selection guidelines		19
B.1	General	19
B.2	Selection parameters	19
B.3	Actuator selection	20
B.3.1	General	20
B.3.2	Torque characteristics for rack and pinion or vane actuators	21
B.3.3	Torque characteristics for scotch yoke actuators (e.g. symmetric system)	22
Bibliography		23