

DIN EN 15714-4:2010-02 (E)

Industrial valves - Actuators - Part 4: Hydraulic part-turn actuators for industrial valves - Basic requirements

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Classification and designation	5
3.1	General	5
3.2	Action	6
3.3	Valve actuator attachment	6
3.4	Motive energy	6
3.4.1	Operating medium	6
3.4.2	Quality	6
3.4.3	Pressure	6
4	Design requirements	6
4.1	General	6
4.2	Output torques (performance test)	7
4.3	Pressure ratings and endurance	7
4.3.1	Pressure ratings	7
4.3.2	Endurance	7
4.4	Minimum moving pressure	8
4.5	Leakage	8
4.6	Moving time	8
4.7	Angle	9
4.8	Fluid displacement volume	9
4.9	Environmental conditions	9
4.9.1	Ambient temperature	9
4.9.2	Enclosure protection	9
4.9.3	Corrosion protection	9
4.10	Basic design	10
4.10.1	Safety requirements	10
4.10.2	Part-turn valve actuator attachment	10
4.10.3	Pressure connections	11
4.10.4	Fail safe direction for spring return actuators	12
4.10.5	Mechanical safety factors	12
4.11	Position indication	12
4.12	Optional equipment	13
4.12.1	Ancillaries	13
4.12.2	Manual operation	15
4.12.3	End stop adjustment	15
5	Conformity assessment	15
5.1	General	15
5.2	Type tests	16
5.3	Control of production process and quality system	16
6	Marking	17
7	Actuator selection guidelines	18

8	Documentation	18
	Annex A (normative) Endurance test procedure	19
A.1	General	19
A.2	Test equipment	19
A.3	Test conditions	19
A.4	Test procedure	19
A.4.1	Design life	19
A.4.2	Output torque testing	19
A.4.3	Pressure testing	19
A.4.4	Hydraulic testing	20
A.5	Acceptance criteria	20
	Annex B (informative) Actuator selection guidelines	21
B.1	General	21
B.2	Selection parameters	21
B.3	Actuator selection	22
B.3.1	General	22
B.3.2	Torque characteristics for rack and pinion or linear helical spline actuators	23
B.3.3	Torque characteristics for scotch yoke actuators (e.g. symmetric system)	24
	Bibliography	25