

DIN EN ISO 4126-4:2013-12 (E)

Safety devices for protection against excessive pressure - Part 4: Pilot operated safety valves (ISO 4126-4:2013)

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Symbols and units	8
5	Design	8
5.1	General	8
5.2	Valve end connections	9
5.3	Minimum requirements for springs	9
5.4	Materials	10
6	Production testing	10
6.1	Purpose	10
6.2	General	10
6.3	Hydrostatic testing	10
6.4	Pneumatic testing	11
6.5	Adjustment of set or cold differential test pressure	11
6.6	Seat leakage test	12
6.7	Pressure seals	12
7	Type testing	12
7.1	General	12
7.2	Tests to determine operating characteristics	13
7.3	Tests to determine flow characteristics	15
7.4	Determination of the coefficient of discharge	17
7.5	Certification of coefficient of discharge	17
8	Determination of pilot operated safety valve performance	17
9	Sizing of pilot operated safety valves	17
10	Marking and sealing	17
10.1	Marking	17
10.2	Sealing of a pilot operated safety valve	18
Annex ZA (informative) Relationship between this International Standard and the Essential Requirements of EU Directive 97/23/EC (PED)		19
Bibliography		20