DIN EN ISO 4126-7:2013-12 (E)

Safety devices for protection against excessive pressure - Part 7: Common data (ISO 4126-7:2013)

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Symbols and units 6

5 Determination of safety valve performance 7
5.1 Determination of coefficient of discharge 7
5.2 Critical and subcritical flow 7
5.3 Discharge capacity at critical flow 7
5.4 Discharge capacity for any gas at subcritical flow 8
5.5 Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000 8

6 Sizing of safety valves 9
6.1 General 9
6.2 Valves for gas or vapour relief 9
6.3 Calculation of capacity 9

7 Thermodynamic properties 11
7.1 Steam data 11
7.2 Value of C as a function of k 11
7.3 Theoretical capacity correction factors for sub-critical flow (Kb) 11
7.4 Estimating chart for compressibility factor, Z 22
7.5 Capacity correction factor for viscosity, Kv 24
7.6 Properties of gases 25

8 Minimum requirements for helical compression springs 26
8.1 General 26
8.2 Materials 26
8.3 Marking 26
8.4 Dimensions 27
8.5 Spring plates/buttons 27
8.6 Inspection, testing and tolerances 27

9 Minimum requirements for safety valve disc springs 30
9.1 General 30
9.2 Materials 30
9.3 Marking 30
9.4 Dimensions 30
9.5 Inspection, testing and tolerances 30

Annex A (informative) Examples of capacity calculations for various media 31

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC (PED) 36

Bibliography 37