

DIN EN 15091:2014-03 (E)

Sanitary tapware - Electronic opening and closing sanitary tapware

Contents		Page
Foreword		5
Introduction		6
1	Scope	7
2	Normative references	9
3	Terms and definitions	10
4	General requirements and testing	11
4.1	Marking	11
4.2	Materials	11
4.2.1	Chemical and hygienic requirements	11
4.2.2	Exposed surface conditions	11
4.3	Functions	11
4.4	Protection against pollution	11
4.5	Electric characteristics and requirements	11
4.5.1	General	11
4.5.2	Electrical safety	11
4.5.3	Electrical operation of solenoid valves	12
4.5.4	Electric strength and insulation resistance of the solenoid valve	12
4.5.5	Operational safety	12
4.6	Leaktightness characteristics	13
4.6.1	General	13
4.6.2	Principle	13
4.6.3	Apparatus	14
4.6.4	Leaktightness of tapware upstream of the obturator	14
4.6.5	Leaktightness of tapware downstream of the obturator with the obturator open	14
4.6.6	Leaktightness tests - Summary table	14
4.7	Pressure resistance characteristics - mechanical performance under pressure	15
4.7.1	General	15
4.7.2	Principle	15
4.7.3	Apparatus	15
4.7.4	Procedure	15
4.7.5	Requirements	15
5	Requirements and testing for tapware	15
5.1	Scope	15
5.2	Dimensional characteristics	15
5.2.1	General	15
5.2.2	Tap with visible body for horizontal surfaces	15
5.2.3	Taps with visible body for mounting on vertical surfaces	17
5.2.4	In-line tapware with threaded inlet and outlet	17
5.2.5	Concealed tapware for vertical surfaces	18
5.2.6	Mixing valves for horizontal surface	18
5.2.7	Mixing valves with visible body for mounting on vertical surfaces with captive nuts and eccentric unions	20
5.2.8	Mixing valves with opposed inlets	20
5.2.9	Nozzle outlets for use with flow rate regulators	22
5.2.10	Special cases	22
5.3	Hydraulic characteristics	22

5.3.1	General	22
5.3.2	Test apparatus for tapware intended for Type 1 water supply systems	23
5.3.3	Principle of the flow test	26
5.3.4	Requirements	27
5.3.5	Cross flow between hot and cold water	27
5.4	Water hammer	27
5.4.1	Principle of water hammer test	27
5.4.2	Test apparatus	28
5.4.3	Procedure	28
5.4.4	Requirements	29
5.5	Endurance	29
5.5.1	General	29
5.5.2	Principle	29
5.5.3	Procedure for single taps	29
5.5.4	Procedure for mixers	30
5.5.5	Requirements	30
5.6	Acoustic characteristics	30
5.6.1	General	30
5.6.2	Procedure	31
5.6.3	Requirements	31
6	Requirements and testing for flushing valves for urinals	32
6.1	Scope	32
6.2	Definitions	32
6.2.1	Single flush urinal valves	32
6.2.2	Siphon action flushing urinal valves	32
6.2.3	Isolating valves for flushing urinal valves	32
6.3	Classification of flushing urinal valves	32
6.4	Designation	33
6.5	Dimensional characteristics	33
6.6	Hydraulic characteristics	34
6.6.1	General	34
6.6.2	Test method	34
6.7	Measurement of water hammer for urinal flushing valves	35
6.7.1	Principle of water hammer test	35
6.7.2	Test apparatus	35
6.7.3	Procedure	35
6.7.4	Requirements	36
6.8	Mechanical endurance	36
6.8.1	General	36
6.8.2	Apparatus	36
6.8.3	Procedure	36
6.8.4	Requirements	37
7	Requirements and testing for flushing valves for WCs	37
7.1	Scope	37
7.2	Definitions	37
7.3	Classification	38
7.3.1	General	38
7.3.2	6 l and 6 to 9 l valves	38
7.3.3	9 l valves	38
7.4	Dimensional characteristics	38
7.5	Hydraulic characteristics	39
7.5.1	General	39
7.5.2	Test method	39
7.5.3	Testing of the flow rate / Impact force at lower dynamic pressure	43
7.5.4	Testing of the flow rate / Volume at lower dynamic pressure	44
7.5.5	Testing of flush flow rate / impact force at upper dynamic pressure	45
7.5.6	Measurement of water hammer	46
7.6	Principle and verification of atmospheric pipe interrupters of WC flushing valves	46
7.7	Mechanical endurance	47
7.7.1	General	47

7.7.2	Procedure	47
7.7.3	Minimum requirements	47
7.8	Acoustic characteristics	47
Annex A (normative) Design of pressure take-off tees		48
Annex B (informative) Potential consequences of use outside the recommended operating limits ...		50
Bibliography		51