ISO 4126-7:2013-07 (E)

Safety devices for protection against excessive pressure - Part 7: Common data

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and units 3

5 Determination of safety valve performance 4
5.1 Determination of coefficient of discharge 4
5.2 Critical and subcritical flow 4
5.3 Discharge capacity at critical flow 4
5.4 Discharge capacity for any gas at subcritical flow 5
5.5 Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000 5

6 Sizing of safety valves 6
6.1 General 6
6.2 Valves for gas or vapour relief 6
6.3 Calculation of capacity 6

7 Thermodynamic properties 8
7.1 Steam data 8
7.2 Value of C as a function of k 8
7.3 Theoretical capacity correction factors for sub-critical flow (Kb) 8
7.4 Estimating chart for compressibility factor, Z 19
7.5 Capacity correction factor for viscosity, Kv 21
7.6 Properties of gases 22

8 Minimum requirements for helical compression springs 23
8.1 General 23
8.2 Materials 23
8.3 Marking 23
8.4 Dimensions 24
8.5 Spring plates/buttons 24
8.6 Inspection, testing and tolerances 24

9 Minimum requirements for safety valve disc springs 27
9.1 General 27
9.2 Materials 27
9.3 Marking 27
9.4 Dimensions 27
9.5 Inspection, testing and tolerances 27

Annex A (informative) Examples of capacity calculations for various media 28

Bibliography 33