

ISO 4126-7:2013-07 (E)

Safety devices for protection against excessive pressure - Part 7: Common data

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	3
5	Determination of safety valve performance	4
5.1	Determination of coefficient of discharge	4
5.2	Critical and subcritical flow	4
5.3	Discharge capacity at critical flow	4
5.4	Discharge capacity for any gas at subcritical flow	5
5.5	Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000	5
6	Sizing of safety valves	6
6.1	General	6
6.2	Valves for gas or vapour relief	6
6.3	Calculation of capacity	6
7	Thermodynamic properties	8
7.1	Steam data	8
7.2	Value of C as a function of k	8
7.3	Theoretical capacity correction factors for sub-critical flow (K_b)	8
7.4	Estimating chart for compressibility factor, Z	19
7.5	Capacity correction factor for viscosity, K_v	21
7.6	Properties of gases	22
8	Minimum requirements for helical compression springs	23
8.1	General	23
8.2	Materials	23
8.3	Marking	23
8.4	Dimensions	24
8.5	Spring plates/buttons	24
8.6	Inspection, testing and tolerances	24
9	Minimum requirements for safety valve disc springs	27
9.1	General	27
9.2	Materials	27
9.3	Marking	27
9.4	Dimensions	27
9.5	Inspection, testing and tolerances	27
Annex A (informative) Examples of capacity calculations for various media		28
Bibliography		33