

DIN EN ISO 4126-7:2016-12 (E)

Safety devices for protection against excessive pressure - Part 7: Common data (ISO 4126-7:2013 + Amd 1:2016) (includes Amendment A1:2016)

Contents		Page
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Symbols and units	9
5	Determination of safety valve performance	10
5.1	Determination of coefficient of discharge	10
5.2	Critical and subcritical flow	10
5.3	Discharge capacity at critical flow	10
5.4	Discharge capacity for any gas at subcritical flow	11
5.5	Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000	11
6	Sizing of safety valves	12
6.1	General	12
6.2	Valves for gas or vapour relief	12
6.3	Calculation of capacity	12
7	Thermodynamic properties	14
7.1	Steam data	14
7.2	Value of C as a function of k	14
7.3	Theoretical capacity correction factors for sub-critical flow (K_b)	14
7.4	Estimating chart for compressibility factor, Z	25
7.5	Capacity correction factor for viscosity, K_v	27
7.6	Properties of gases	28
8	Minimum requirements for helical compression springs	29
8.1	General	29
8.2	Materials	29
8.3	Marking	29
8.4	Dimensions	30
8.5	Spring plates/buttons	30
8.6	Inspection, testing and tolerances	30
9	Minimum requirements for safety valve disc springs	33
9.1	General	33
9.2	Materials	33
9.3	Marking	33
9.4	Dimensions	33
9.5	Inspection, testing and tolerances	33
Annex A (informative) Examples of capacity calculations for various media		34
A.1	Capacity calculations for gaseous media at critical flow (see 6.3.3.1)	34
A.2	Capacity calculations for gaseous media at subcritical flow (see 6.3.3.2)	36
A.3	Capacity calculations for liquids (see 6.3.4)	37

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC (PED)	39
Bibliography	40