

DIN EN 816:2017-10 (E)

Sanitary tapware - Automatic shut-off valves PN 10

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Designation | 7 |
| 5 | Marking - Identification | 7 |
| 5.1 | Marking | 7 |
| 5.2 | Identification | 8 |
| 6 | Materials | 8 |
| 6.1 | Chemical and hygienic characteristics | 8 |
| 6.2 | Exposed surface condition and quality of coating | 8 |
| 7 | Backflow protection | 8 |
| 8 | Dimensional characteristics | 8 |
| 8.1 | General | 8 |
| 8.2 | Tap with visible body for horizontal surfaces (see Figure 1 and Table 3) | 9 |
| 8.3 | Taps with visible body for mounting on vertical surfaces (see Figure 2 and Table 4) | 10 |
| 8.4 | In-line tapware with threaded inlet and outlet | 10 |
| 8.4.1 | Inlets and outlets aligned (see Figure 3 and Table 5) | 10 |
| 8.4.2 | Inlets and outlets at right angles (see Figure 4 and Table 5) | 11 |
| 8.5 | Concealed tapware for vertical surfaces | 11 |
| 8.6 | Mixer for horizontal surface (see Figures 5, 6 and 7 and Table 6) | 12 |
| 8.7 | Mixer with visible body for mounting on vertical surfaces | 16 |
| 8.7.1 | Mixers with parallel inlets | 16 |
| 8.7.2 | Mixer with opposed inlets (see Figure 11 and Table 5) | 18 |
| 8.8 | Nozzle outlets for use with flow rate regulators | 18 |
| 8.9 | Special cases | 18 |
| 8.9.1 | Special taps and mixers for installation on horizontal surfaces | 18 |
| 8.9.2 | Special taps and mixers for installation on vertical surfaces | 19 |
| 9 | Leaktightness characteristics | 19 |
| 9.1 | General | 19 |
| 9.2 | Leaktightness tests | 19 |
| 9.2.1 | Principle | 19 |
| 9.2.2 | Apparatus | 19 |
| 9.2.3 | Leaktightness of tapware upstream of the obturator | 19 |
| 9.2.4 | Leaktightness of tapware downstream of the obturator with the obturator open | 20 |
| 9.3 | Summary of the leaktightness tests | 21 |
| 10 | Pressure resistance characteristics | 22 |
| 10.1 | General | 22 |
| 10.2 | Test of mechanical behaviour | 22 |
| 10.2.1 | Principle | 22 |

| | | |
|--------|---|----|
| 10.2.2 | Apparatus | 22 |
| 10.2.3 | Test of the mechanical behaviour upstream of the obturator, with the obturator in the closed position | 22 |
| 10.2.4 | Test of mechanical behaviour downstream of the obturator, with the obturator in the open position | 22 |
| 10.3 | Summary of the pressure tests | 23 |
| 11 | Hydraulic characteristics | 23 |
| 11.1 | General | 23 |
| 11.2 | Test method | 23 |
| 11.2.1 | Principle | 23 |
| 11.2.2 | Test apparatus | 23 |
| 11.2.3 | Mounting of single self-closing taps | 26 |
| 11.2.4 | Mounting of mixers (see Figures 14 a), 14 b) and 14 c)) | 26 |
| 11.3 | Principle of the flow test | 27 |
| 11.4 | Requirements | 28 |
| 11.4.1 | Flow rate | 28 |
| 11.4.2 | Flow rate curve | 28 |
| 11.4.3 | Flow duration | 28 |
| 11.4.4 | Specific characteristics of mixers | 29 |
| 11.4.5 | Testing at minimum pressure | 31 |
| 12 | Mechanical properties - Operating force | 31 |
| 12.1 | General | 31 |
| 12.2 | Procedure | 31 |
| 12.3 | Requirement | 31 |
| 13 | Mechanical endurance or wear resistance characteristics | 31 |
| 13.1 | General | 31 |
| 13.2 | Procedure | 31 |
| 13.3 | Cycle for a single tap | 32 |
| 13.4 | Cycle for a mixer | 32 |
| 13.5 | Minimum requirements | 32 |
| 14 | Acoustic characteristics | 33 |
| 14.1 | General | 33 |
| 14.2 | Procedure | 33 |
| 14.2.1 | Fitting and operating conditions for tapware | 33 |
| 14.2.2 | Test method | 33 |
| 14.3 | Requirements | 33 |
| 14.3.1 | Expression of the results | 33 |
| 14.3.2 | Determination of the acoustic group | 33 |
| 14.3.3 | Flow class | 34 |
| | Annex A (normative) Pressure take off tees | 35 |
| | Annex B (informative) Acoustic classification (example) | 37 |
| B.1 | Tapware with nozzle | 37 |
| B.2 | Tapware with shower head outlet | 37 |
| B.3 | Tapware with nozzle and shower or shower head outlet | 37 |