

# DIN EN ISO 5211:2017-08 (E)

## Industrial valves - Part-turn actuator attachments (ISO 5211:2017)

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
Foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>7</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>4</b>	<b>Maximum flange torques .....</b>	<b>8</b>
<b>5</b>	<b>Flange dimensions .....</b>	<b>9</b>
<b>6</b>	<b>Designation .....</b>	<b>11</b>
<b>7</b>	<b>Dimensions and torques .....</b>	<b>12</b>
7.1	General .....	12
7.2	Drive by key(s) .....	12
7.3	Drive by parallel or diagonal square head .....	15
7.4	Drive by flat head .....	16
7.5	Drive by improved flat head .....	18
7.6	Drive by involute spline .....	20
7.7	Drive by bi-square .....	21
<b>8</b>	<b>Position of driven components at interface below part-turn actuator .....</b>	<b>22</b>
8.1	Drive by key(s) .....	22
8.2	Drive by parallel or diagonal square head or bi-square .....	24
8.3	Drive by flat head .....	25
<b>9</b>	<b>Dowel pins .....</b>	<b>25</b>
<b>Annex A (informative) Explanation of calculation .....</b>		<b>27</b>
A.1	Basis of torque values for flange sizes .....	27
A.2	Coefficient of friction of 0,2 .....	27
A.3	Tension stress bolts .....	28
Bibliography .....		29