

# ISO 4126-2:2018 (E)

## Safety devices for protection against excessive pressure — Part 2: Bursting disc safety devices

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Materials
4.1	Selection of materials
4.2	Material specifications
4.3	Protection from corrosion
5	Types of bursting discs
5.1	Conventional domed bursting discs (Forward acting)
5.2	Reverse domed bursting discs (Reverse acting)
5.3	Flat bursting discs
5.4	Other types and designs
6	Bursting disc holders
6.1	Design
6.1.1	Pressure-containing capability
6.1.2	Other design requirements
6.2	Types
6.3	Connections
7	Back pressure supports
7.1	General
7.2	Opening back pressure supports
7.3	Non-opening back pressure supports
8	Temperature shields
9	Stiffening rings
10	Gaskets/seals
11	Assembly of bursting disc safety devices
11.1	General
11.2	Bursting disc safety devices with replaceable bursting disc assemblies
11.3	Bursting disc safety devices with non-replaceable bursting disc assemblies
12	Specified bursting pressure requirements
13	Inspection by the manufacturer
14	Test procedures
14.1	General
14.2	Pressure testing
14.3	Burst testing
14.3.1	General

- 14.3.2 Coincident temperature in the range 15 °C to 30 °C
  - 14.3.3 Coincident temperature above or below the range 15 °C to 30 °C
  - 14.3.4 Procedure for burst testing
- 14.4 Leak testing
  - 14.4.1 General
  - 14.4.2 Selection of acceptable leakage rate
- 14.5 Non-destructive examination
- 15 Certification
- 16 Product designation
- 17 Marking
  - 17.1 General
  - 17.2 Bursting discs or bursting disc assemblies
  - 17.3 Bursting disc holders
  - 17.4 Bursting disc safety devices with non-replaceable bursting disc assemblies
  - 17.5 Ancillary components
  - 17.6 Omission of markings
- 18 Packaging and storage
- Annex A (informative) Packaging: marking, assembly instructions and documentation
  - A.1 Marking of packages
  - A.2 Provision of assembly and installation instructions
  - A.3 Provision of documents, loose identification plates, etc.

Page count: 21