

# DIN EN 13434:2022-04 (E)

## Devices to prevent pollution by backflow of potable water - Mechanical disconnector, flow actuated - Family G, Type B

---

### Contents

|  | Page |
|--|------|
| European foreword .....  | 4    |
| Introduction .....   | 5    |
| 1 Scope.....   | 6    |
| 2 Normative references.....  | 6    |
| 3 Terms and definitions .....  | 7    |
| 4 Denomination.....  | 9    |
| 5 Designation .....  | 9    |
| 6 Symbolization.....   | 9    |
| 7 Physical-chemical characteristics.....   | 10   |
| 7.1 General.....   | 10   |
| 7.2 Materials .....  | 10   |
| 7.2.1 General.....   | 10   |
| 7.2.2 Dezincification resistant copper alloy .....   | 10   |
| 7.3 Surface of the body .....  | 10   |
| 7.3.1 General.....   | 10   |
| 7.3.2 Epoxy Coating .....  | 10   |
| 7.3.3 Polyamide Powder based Coating .....   | 10   |
| 7.3.4 Other coatings .....   | 10   |
| 8 Design.....  | 11   |
| 8.1 General.....   | 11   |
| 8.2 Relief valve/Obturator.....  | 11   |
| 8.2.1 General requirements .....   | 11   |
| 8.2.2 Mechanical Disconnector Family G, Type B.....  | 11   |
| 8.3 Disconnection distance.....  | 12   |
| 9 Characteristics and tests .....  | 12   |
| 9.1 General.....   | 12   |
| 9.2 General tolerances .....   | 12   |
| 9.2.1 Tolerance of set parameters .....  | 12   |
| 9.2.2 Accuracy of measuring instruments .....  | 12   |
| 9.3 Expression of the results .....  | 12   |
| 9.4 Dimensional characteristics .....  | 12   |
| 9.4.1 Connections.....   | 12   |
| 9.4.2 Pressure tapping .....   | 12   |
| 9.5 Mechanical characteristics .....   | 13   |
| 9.5.1 General.....   | 13   |
| 9.5.2 Mechanical resistance of the body under pressure .....                                     | 13   |
| 9.5.3 Endurance.....   | 14   |
| 9.5.4 Torque test of Captive rotating Nuts and Bending Strength – Tightness of the Body          | 15   |
| 9.6 Leak tightness characteristics.....  | 16   |
| 9.6.1 Verification of the leak tightness of the downstream check valve in closing direction..... | 16   |
| 9.6.2 Verification of the leak tightness of check valve device (opening direction) .....         | 17   |

|  |   |           |
|--|---|-----------|
| <b>9.6.3</b>   | <b>Verification of the leak tightness of the upstream spring loaded obturator in drain position at low pressure (in the opening direction).....</b> | <b>17</b> |
| <b>9.7</b>   | <b>Hydraulic characteristics.....</b>   | <b>18</b> |
| <b>9.7.1</b>   | <b>Test rig— General circuit.....</b>   | <b>18</b> |
| <b>9.7.2</b>   | <b>Verification of the pressure loss as a function of flow rate .....</b>   | <b>19</b> |
| <b>9.7.3</b>   | <b>Verification of the opening and closing pressures of relief valve .....</b>  | <b>20</b> |
| <b>9.7.4</b>   | <b>Verification of the relief valve flow rate.....</b>  | <b>20</b> |
| <b>9.8</b>   | <b>Compatibility with the products used for shock disinfection of the networks .....</b>  | <b>21</b> |
| <b>9.8.1</b>   | <b>Requirement.....</b>   | <b>21</b> |
| <b>9.8.2</b>   | <b>Test method.....</b>   | <b>21</b> |
| <b>9.9</b>   | <b>Acoustic tests.....</b>  | <b>21</b> |
| <b>9.9.1</b>   | <b>General .....</b>  | <b>21</b> |
| <b>9.9.2</b>   | <b>Procedure .....</b>  | <b>21</b> |
| <b>10</b>  | <b>Order of testing .....</b>   | <b>22</b> |
| <b>11</b>  | <b>Marking and technical documents .....</b>  | <b>23</b> |
| <b>11.1</b>  | <b>General .....</b>  | <b>23</b> |
| <b>11.2</b>  | <b>Marking .....</b>  | <b>23</b> |
| <b>11.3</b>  | <b>Technical documents .....</b>  | <b>24</b> |
| <b>12</b>  | <b>Presentation at delivery.....</b>  | <b>24</b> |
| <b>Annex A (informative) Examples of presentation of test results.....</b> |   | <b>25</b> |
| <b>Bibliography .....</b>  |   | <b>28</b> |