

# DIN EN 15714-5:2022-10 (E)

## Industrial valves - Actuators - Part 5: Pneumatic linear actuators for industrial valves - Basic requirements

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	5
4	Classification/designation .....	7
4.1	Duty classification .....	7
4.1.1	General .....	7
4.1.2	On-off duty .....	7
4.1.3	Modulating duty .....	7
4.2	Action .....	8
4.2.1	Double acting (DA) .....	8
4.2.2	Single acting (SA) .....	8
5	Motive energy .....	8
5.1	Operating medium .....	8
5.2	Quality .....	8
5.3	Pressure .....	8
6	Actuator performance data .....	9
6.1	Minimum moving pressure .....	9
6.2	Operating time .....	9
6.3	Displacement volume .....	9
6.4	Dimensions and performances for double acting version .....	9
6.5	Dimensions and performances for single acting version .....	11
7	Basic design requirements .....	12
7.1	Safety requirements .....	12
7.2	Linear actuator attachment .....	12
7.3	Nominal stroke .....	13
7.4	Endurance of linear actuators .....	13
7.5	Leakage .....	14
7.6	Environmental conditions .....	15
7.6.1	Ambient temperature .....	15
7.6.2	Enclosure protection .....	15
7.6.3	Corrosion protection .....	15
7.7	Pressure connections .....	17
7.7.1	General .....	17
7.7.2	Remotely mounted pilot valves .....	17
7.7.3	Direct mounted pilot valves .....	18
7.8	Structural safety factors .....	19
8	Optional equipment .....	20
8.1	Ancillaries .....	20
8.2	Manual operation device .....	20
8.3	Mechanical end stop adjustment .....	20
8.4	Position indication .....	21
8.5	Bracket .....	21

8.6	Anti-rotation device .....	21
9	Conformity assessment .....	21
9.1	General .....	21
9.2	Type tests .....	21
9.3	Control of production process .....	22
10	Marking .....	24
10.1	Mandatory marking .....	24
10.2	Optional marking .....	24
11	Documentation .....	25
12	Linear actuator selection guidelines .....	25
Annex A (normative) Endurance test procedure .....		26
Annex B (informative) Actuator selection guidelines .....		28
Bibliography .....		31