

DIN EN 15714-6:2023-03 (E)

Industrial valves - Actuators - Part 6: Hydraulic linear actuators for industrial valves - Basic requirements

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Classification/Designation | 7 |
| 4.1 | Duty classification | 7 |
| 4.1.1 | General | 7 |
| 4.1.2 | On-off duty | 7 |
| 4.1.3 | Modulating duty | 7 |
| 4.2 | Action | 7 |
| 4.2.1 | Double Acting (DA) | 7 |
| 4.2.2 | Single Acting (SA) | 7 |
| 5 | Motive energy | 7 |
| 5.1 | Operating medium | 7 |
| 5.2 | Quality | 8 |
| 5.3 | Pressure | 8 |
| 5.3.1 | General | 8 |
| 5.3.2 | Maximum allowable pressure (MAP) | 8 |
| 5.3.3 | Design pressure | 8 |
| 5.3.4 | Working pressure | 8 |
| 5.3.5 | Structural test pressure | 8 |
| 5.3.6 | Minimum moving pressure | 8 |
| 6 | Actuator basic performances | 9 |
| 6.1 | Double acting version | 9 |
| 6.2 | Single acting version | 10 |
| 6.3 | Displacement volume | 10 |
| 6.4 | Operating time | 10 |
| 7 | Basic design requirements | 10 |
| 7.1 | Safety requirements | 10 |
| 7.2 | Linear actuator attachment | 11 |
| 7.3 | Attachments size | 12 |
| 7.4 | Nominal stroke | 12 |
| 7.5 | Endurance | 13 |
| 7.5.1 | General | 13 |
| 7.5.2 | Double acting version | 13 |
| 7.5.3 | Single acting version | 13 |
| 7.6 | Leakage | 13 |
| 7.7 | Environmental conditions | 14 |
| 7.7.1 | Ambient temperature | 14 |
| 7.7.2 | Enclosure protection | 14 |
| 7.7.3 | Corrosion protection | 14 |
| 7.8 | Pressure connections | 15 |
| 7.8.1 | General | 15 |
| 7.8.2 | Remotely mounted pilot valves | 16 |

| | | |
|---|--|----|
| 7.8.3 | Direct mounted pilot valves | 17 |
| 7.9 | Structural safety factors | 18 |
| 8 | Optional equipment | 18 |
| 8.1 | General | 18 |
| 8.2 | Ancillaries | 18 |
| 8.3 | Manual operation device | 19 |
| 8.4 | Mechanical end stop | 19 |
| 8.5 | Position indicator | 19 |
| 8.6 | Bracket | 19 |
| 8.7 | Anti-rotation device | 19 |
| 9 | Conformity assessment | 19 |
| 9.1 | General | 19 |
| 9.2 | Type tests | 19 |
| 9.3 | Control of production process | 20 |
| 10 | Marking | 22 |
| 10.1 | Mandatory requirements | 22 |
| 10.2 | Optional requirements | 22 |
| 11 | Documentation | 23 |
| 12 | Linear actuator selection guidelines | 23 |
| Annex A (normative) Endurance test procedure | | 24 |
| A.1 | General | 24 |
| A.2 | Test equipment | 24 |
| A.3 | Test conditions | 24 |
| A.4 | Test procedure | 24 |
| A.5 | Acceptance criteria | 25 |
| Annex B (informative) Actuator selection guidelines | | 26 |
| B.1 | General | 26 |
| B.2 | Selection parameters | 26 |
| B.2.1 | General | 26 |
| B.2.2 | Valve questions | 26 |
| B.2.3 | Actuator questions | 27 |
| B.2.4 | Ancillary questions | 27 |
| B.2.5 | Environmental conditions | 27 |
| B.3 | Actuator selection | 27 |
| Annex C (informative) Guideline to establish the basic performances for single acting version | | 28 |
| C.1 | General | 28 |
| C.2 | Specific thrusts definitions relevant to the single acting version | 28 |
| C.3 | Criteria for performances selection | 28 |
| Bibliography | | 30 |