DIN EN 200:2024-05 (E)

Sanitary tapware - Single taps and combination taps for water supply systems of type 1 and type 2 - General technical specification

Contents

Page

European foreword 7

Introduction 8

1 Scope 9

2 Normative references 11

3 Terms and definitions 12

4 Designation 15

5 Marking and identification 16
5.1 Marking 16
5.2 Identification 16
5.2.1 Identification of inlets 16
5.2.2 Identification of flow controls equipment 16

6 Materials 17
6.1 Chemical and hygiene requirements 17
6.2 Exposed surface condition and quality of coating 17

7 Backflow protection 17

8 Sequence of testing 17

9 Dimensional characteristics 17
9.1 General remarks 17
9.2 Inlet dimensions 18
9.3 Outlet dimensions 20
9.4 Mounting dimensions 24
9.5 Special cases 26

10 Leaktightness characteristics 27
10.1 Principle 27
10.2 Apparatus 27
10.3 Leaktightness of the obturator and of the tap upstream of the obturator(s) with the obturator in the closed position 27
10.3.1 Procedure 27
10.3.2 Requirements 27
10.4 Leaktightness downstream of the obturator 27
10.4.1 General 27
10.4.2 Procedure 27
10.4.3 Requirements 28
10.5 Leaktightness of manually operated diverters 28
10.5.1 General 28
10.5.2 Procedure 28
10.5.3 Procedure where an outlet(s) cannot be artificially closed – products for type 1 systems 28
10.5.4 Procedure where an outlet(s) cannot be artificially closed – products for type 2 systems 29
10.5.5 Requirements 29
10.6 Leaktightness and operation of diverters with automatic return (and semi-automatic type diverters) 29
10.6.1 General 29
10.6.2 Procedure – products for Type 1 systems 29

10.6.3 Procedure – products for Type 2 systems 30
10.6.4 Requirements 31

11 Pressure resistance 33
11.1 Principle 33
11.2 Apparatus 33
11.3 Mechanical behaviour upstream of the obturator – obturator in the closed position 33
11.3.1 Procedure 33
11.3.2 Requirement 33
11.4 Mechanical behaviour downstream of the obturator – obturator in the open position 33
11.4.1 Procedure for products for type 1 systems 33
11.4.2 Procedure for products for type 2 systems 33
11.4.3 Requirement 34

12 Hydraulic performance 34
12.1 General 34
12.2 Determination of flow rate – products for type 1 systems 35
12.2.1 Principle 35
12.2.2 Apparatus 35
12.2.3 Procedure 35
12.2.4 Requirements 35
12.3 Determination of flow rate – products for type 2 systems 36
12.3.1 Principle 36
12.3.2 Apparatus 36
12.3.3 Procedure 37
12.3.4 Requirements 37

13 Mechanical strength/torsional resistance 38
13.1 Principle 38
13.2 Apparatus 38
13.3 Test piece 38
13.4 Procedure 38
13.5 Requirements 38

14 Mechanical endurance 38
14.1 General 38
14.2 Endurance test for on/off flow control devices operated by rotating the control handle 39
14.2.1 Principle 39
14.2.2 Apparatus 39
14.2.3 Procedure 39
14.2.4 Requirement 41
14.3 Endurance test for other on/off flow control devices 42
14.3.1 Principle 42
14.3.2 Apparatus 42
14.3.3 Procedure 42
14.3.4 Requirement 42
14.4 Endurance of manually operated diverters 42
14.4.1 Principle 42
14.4.2 Apparatus 43
14.4.3 Procedure 43
14.4.4 Requirement 43
14.5 Endurance of diverters with automatic return 43
14.5.1 Principle 43
14.5.2 Apparatus 43
14.5.3 Procedure 44

14.5.4 Requirement **44**
14.6 Endurance test for swivel spouts **45**
14.6.1 Principle **45**
14.6.2 Apparatus **45**
14.6.3 Procedure for single outlet type **45**
14.6.4 Procedure for divided outlet type **45**
14.6.5 Requirements **46**
15 Acoustic characteristics — products for type 1 systems only **47**
15.1 General **47**
15.2 Procedure **47**
15.2.1 Flow rate class of sanitary tapware products (with appropriate acoustic information) **47**
15.2.2 Flow rate class of sanitary tapware products (without appropriate acoustic information) **47**
15.3 Expression of results **47**
15.3.1 Determination of acoustic group **48**
15.3.2 Correspondence between flow rate classes and measurements **48**
Annex A (informative) **Pressure take-off tee** **49**
Annex B (informative) **Minimum flow rates and test pressures according to application** **52**
Annex C (informative) **Product components (detailed by other standards)** **53**
Bibliography **54**

Figures

Figure 1 — Supply system of Type 1 with a pressure range of (0,05 to 1,0) MPa [(0,5 to 10) bar] **10**
Figure 2 — Supply system of Type 2 with a pressure range of (0,01 to 1,0) MPa [(0,1 to 10) bar] **11**
Figure 3 — Bib taps 1/2 and 3/4 – single hole taps **19**
Figure 4 — Multi hole combination taps **20**
Figure 5 — Supply connections for taps and remote outlets **20**
Figure 6 — Pillar and bib taps **22**
Figure 7 — Remote outlet **22**
Figure 8 — Single hole combination tap/remote outlet **23**
Figure 9 — Bath/shower combination tap/remote outlet **23**
Figure 10 — Single hole taps **25**
Figure 11 — Two-hole tap (fixed centres) **26**
Figure 12 — Three-hole tap (adjustable centres) **26**
Figure 13 — Clamping Arrangement for use with ceramic sanitaryware **26**
Figure 14 — Apparatus for testing the leaktightness of automatic diverters for taps for supply system of Type 2 ..... **31**
Figure 15 — Flow rate test apparatus for sanitary tapware for Type 2 systems **37**
Figure 16 — Life test –closing torque vs time **41**
Figure 17 — Endurance test rig for divided-outlet swivel spout **46**
Figure A.1 — Pressure take-off tee (test rig Type 1 taps) **49**
Figure A.2 — Schematic examples of pressure take-off tees (test rig Type 1 taps) **51**

Tables

Table 1 — Conditions of use **9**
Table 2 — Designation **15**
Table 3 — Sequence of testing **17**
Table 4 — Inlet dimensions sanitary tapware **18**
Table 5 — Outlet dimensions **21**
Table 6 — Mounting dimensions **24**
Table 7 — Informative summary of leaktightness tests **32**
Table 8 — Informative summary of pressure resistance tests **34**
Table 9 — Informative summary of test conditions for on/off flow control devices **40**
Table 10 — Informative summary of test conditions for diverters **44**
Table 11 — Informative summary of test conditions for swivel spout **47**
Table 12 — Acoustic group **48**
Table 13 — Flow rate classes (EN ISO 3822-4) **48**
Table A.1 — Dimensions of the pressure take-off tee **50**
Table B.1 —Recommended flow rates for domestic use **52**