

DIN EN 15091:2025-11 (E)

Sanitary tapware - Electronic opening and closing sanitary tapware (includes Corrigendum :2025)

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 5 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 10 |
| 3 | Terms and definitions | 11 |
| 4 | General requirements and testing | 11 |
| 4.1 | Marking | 11 |
| 4.2 | Identification | 11 |
| 4.3 | Materials | 11 |
| 4.3.1 | Chemical and hygienic requirements | 11 |
| 4.3.2 | Exposed surface conditions | 11 |
| 4.4 | Functions | 12 |
| 4.5 | Backflow protection | 12 |
| 4.6 | Electric characteristics and requirements | 12 |
| 4.6.1 | General | 12 |
| 4.6.2 | Electrical safety | 12 |
| 4.6.3 | Electrical operation of solenoid valves | 13 |
| 4.6.4 | Electric strength and insulation resistance of the solenoid valve | 13 |
| 4.6.5 | Operational safety | 13 |
| 4.7 | Leaktightness characteristics | 14 |
| 4.7.1 | General | 14 |
| 4.7.2 | Principle | 14 |
| 4.7.3 | Apparatus | 14 |
| 4.7.4 | Leaktightness of tapware upstream of the obturator | 14 |
| 4.7.5 | Leaktightness of tapware downstream of the obturator with the obturator open | 14 |
| 4.7.6 | Leaktightness tests - Summary table | 15 |
| 4.8 | Pressure resistance characteristics - mechanical performance under pressure | 15 |
| 4.8.1 | General | 15 |
| 4.8.2 | Principle | 15 |
| 4.8.3 | Apparatus | 15 |
| 4.8.4 | Procedure | 15 |
| 4.8.5 | Requirements | 16 |
| 5 | Requirements and testing for tapware | 16 |
| 5.1 | General | 16 |
| 5.2 | Dimensional characteristics | 16 |
| 5.2.1 | General | 16 |
| 5.2.2 | Tap with visible body for horizontal surfaces | 16 |
| 5.2.3 | Taps with visible body for mounting on vertical surfaces | 18 |
| 5.2.4 | In-line tapware with threaded inlet and outlet | 18 |
| 5.2.5 | Concealed tapware for vertical surfaces | 19 |
| 5.2.6 | Mixing valves for horizontal surface | 19 |
| 5.2.7 | Mixing valves with visible body for mounting on vertical surfaces with captive nuts and eccentric unions | 21 |
| 5.2.8 | Mixing valves with opposed inlets | 21 |
| 5.2.9 | Nozzle outlets for use with aerators with integrated flow regulators | 22 |

| | | |
|--------|---|----|
| 5.2.10 | Special cases | 22 |
| 5.3 | Hydraulic characteristics | 23 |
| 5.3.1 | General | 23 |
| 5.3.2 | Test apparatus for tapware intended for Type 1 water supply systems | 23 |
| 5.3.3 | Principle of the flow test | 27 |
| 5.3.4 | Requirements | 28 |
| 5.3.5 | Cross flow between hot and cold water | 28 |
| 5.4 | Water hammer | 28 |
| 5.4.1 | Principle of water hammer test | 28 |
| 5.4.2 | Test apparatus | 28 |
| 5.4.3 | Procedure | 29 |
| 5.4.4 | Requirements | 30 |
| 5.5 | Endurance | 30 |
| 5.5.1 | General | 30 |
| 5.5.2 | Principle | 30 |
| 5.5.3 | Procedure for single taps | 30 |
| 5.5.4 | Procedure for mixers | 30 |
| 5.5.5 | Requirements | 31 |
| 5.6 | Acoustic characteristics | 31 |
| 5.6.1 | General | 31 |
| 5.6.2 | Procedure | 31 |
| 5.6.3 | Requirements | 32 |
| 6 | Requirements and testing for flushing valves for urinals | 33 |
| 6.1 | General | 33 |
| 6.2 | Definitions | 33 |
| 6.2.1 | Single flush urinal valves | 33 |
| 6.2.2 | Siphon action flushing urinal valves | 33 |
| 6.2.3 | Isolating valves for flushing urinal valves | 33 |
| 6.3 | Classification of flushing urinal valves | 33 |
| 6.4 | Designation | 33 |
| 6.5 | Dimensional characteristics | 34 |
| 6.6 | Hydraulic characteristics | 35 |
| 6.6.1 | General | 35 |
| 6.6.2 | Test method | 35 |
| 6.7 | Measurement of water hammer for urinal flushing valves | 35 |
| 6.7.1 | Principle of water hammer test | 35 |
| 6.7.2 | Test apparatus | 36 |
| 6.7.3 | Procedure | 36 |
| 6.7.4 | Requirements | 36 |
| 6.8 | Mechanical endurance | 37 |
| 6.8.1 | General | 37 |
| 6.8.2 | Apparatus | 37 |
| 6.8.3 | Procedure | 37 |
| 6.8.4 | Requirements | 37 |
| 7 | Requirements and testing for flushing valves for WCs | 37 |
| 7.1 | General | 37 |
| 7.2 | Definitions | 38 |
| 7.3 | Classification | 38 |
| 7.3.1 | General | 38 |
| 7.4 | Dimensional characteristics | 39 |
| 7.5 | Hydraulic characteristics | 40 |
| 7.5.1 | General | 40 |
| 7.5.2 | Test method | 40 |
| 7.5.3 | Testing of the flow rate/impact force at lower dynamic pressure | 44 |
| 7.5.4 | Testing of the flow rate/Volume at lower dynamic pressure | 44 |
| 7.5.5 | Testing of flush flow rate/impact force at upper dynamic pressure | 46 |
| 7.5.6 | Measurement of water hammer | 48 |
| 7.6 | Principle and verification of atmospheric pipe interrupters of WC flushing valves | 48 |
| 7.7 | Mechanical endurance | 48 |
| 7.7.1 | General | 48 |

| | | |
|---|---------------------------------------|-----------|
| 7.7.2 | Procedure | 48 |
| 7.7.3 | Minimum requirements | 48 |
| 7.8 | Acoustic characteristics | 48 |
| Annex A (normative) Design of pressure take-off tees | | 49 |
| Annex B (informative) Potential consequences of use outside the recommended operating limits ... | | 51 |
| Annex C (informative) Minimum flow rates and test pressures according to application | | 52 |
| Bibliography | | 53 |