

DIN EN 13828:2025-04 (E)

Building valves - Manually operated copper alloy and stainless steel ball valves for potable water supply in buildings - Tests and requirements

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Designation | 7 |
| 5 | Design characteristics | 8 |
| 5.1 | Materials | 8 |
| 5.1.1 | General | 8 |
| 5.1.2 | Body materials | 8 |
| 5.1.3 | Corrosion resistance | 8 |
| 5.1.4 | Anti corrosive layer of the ball | 8 |
| 5.2 | Connection ends | 8 |
| 5.2.1 | General | 8 |
| 5.2.2 | Special cases | 11 |
| 5.3 | Operation | 11 |
| 5.3.1 | Closing direction | 11 |
| 5.3.2 | Operating devices | 11 |
| 5.3.3 | Connection between valve and actuator | 11 |
| 5.4 | Stops | 11 |
| 5.5 | Flow way area | 12 |
| 5.5.1 | Full bore | 12 |
| 5.5.2 | Reduced bore | 12 |
| 5.6 | Test and/or drainage points (design and position) | 12 |
| 6 | Performance characteristics | 13 |
| 6.1 | Test sequence | 13 |
| 6.2 | General | 14 |
| 6.3 | Operating torque | 14 |
| 6.3.1 | Apparatus | 14 |
| 6.3.2 | Procedure | 14 |
| 6.3.3 | Requirements | 14 |
| 6.4 | Resistance against torque | 14 |
| 6.4.1 | Principle | 14 |
| 6.4.2 | Apparatus | 15 |
| 6.4.3 | Procedure | 15 |
| 6.4.4 | Requirements | 16 |
| 6.5 | Resistance against bending | 16 |
| 6.5.1 | Principle | 16 |
| 6.5.2 | Apparatus | 16 |
| 6.5.3 | Procedure | 17 |
| 6.5.4 | Requirements | 18 |
| 6.6 | Torque test of the captive rotating nuts/tail pieces | 18 |
| 6.6.1 | General | 18 |
| 6.6.2 | Procedure | 18 |

| | | |
|--------|--|----|
| 6.6.3 | Requirement | 18 |
| 6.7 | Stop resistance | 19 |
| 6.7.1 | Principle | 19 |
| 6.7.2 | Apparatus | 19 |
| 6.7.3 | Procedure | 19 |
| 6.7.4 | Requirements | 19 |
| 6.8 | Leak-tightness | 19 |
| 6.8.1 | Principle | 19 |
| 6.8.2 | Apparatus | 19 |
| 6.8.3 | Procedure | 19 |
| 6.8.4 | Requirements | 20 |
| 6.9 | Hydraulic strength | 20 |
| 6.9.1 | Principle | 20 |
| 6.9.2 | Apparatus | 20 |
| 6.9.3 | Procedure | 20 |
| 6.9.4 | Requirement | 20 |
| 6.10 | Replenish of water stored in space between ball and body | 20 |
| 6.10.1 | Principle | 20 |
| 6.10.2 | Procedure | 20 |
| 6.10.3 | Requirements | 21 |
| 6.11 | Resistance against pressure jumps | 21 |
| 6.11.1 | Principle | 21 |
| 6.11.2 | Apparatus | 21 |
| 6.11.3 | Test samples | 22 |
| 6.11.4 | Procedure | 22 |
| 6.11.5 | Requirements | 23 |
| 6.12 | Angular seal | 23 |
| 6.12.1 | Principle | 23 |
| 6.12.2 | Apparatus | 23 |
| 6.12.3 | Procedure | 23 |
| 6.12.4 | Requirement | 23 |
| 7 | Acoustic characteristics | 23 |
| 7.1 | General | 23 |
| 7.2 | Principle | 23 |
| 7.3 | Procedure | 24 |
| 7.4 | Determination of acoustic group | 24 |
| 8 | Mechanical endurance characteristics | 24 |
| 8.1 | Resistance against 90 °C water | 24 |
| 8.1.1 | Principle | 24 |
| 8.1.2 | Test installation | 24 |
| 8.1.3 | Conditions | 24 |
| 8.1.4 | Procedure | 25 |
| 8.1.5 | Requirements | 25 |
| 8.2 | Mechanical endurance of the control device | 25 |
| 8.2.1 | Principle | 25 |
| 8.2.2 | Test installation | 25 |
| 8.2.3 | Conditions | 26 |
| 8.2.4 | Procedure | 26 |
| 8.2.5 | Requirements | 26 |
| 9 | Marking | 26 |
| | Bibliography | 28 |