

# DIN EN 15714-4:2025-07 (E)

## Industrial valves - Actuators - Part 4: Hydraulic part-turn actuators for industrial valves - Basic requirements

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and definition .....</b>	<b>5</b>
<b>4</b>	<b>Classification and designation .....</b>	<b>7</b>
<b>4.1</b>	<b>Duty classification .....</b>	<b>7</b>
<b>4.1.1</b>	<b>General .....</b>	<b>7</b>
<b>4.1.2</b>	<b>On-off duty .....</b>	<b>7</b>
<b>4.1.3</b>	<b>Modulating duty .....</b>	<b>7</b>
<b>4.2</b>	<b>Action .....</b>	<b>7</b>
<b>4.2.1</b>	<b>Double acting (DA) .....</b>	<b>7</b>
<b>4.2.2</b>	<b>Single acting (SA) .....</b>	<b>8</b>
<b>5</b>	<b>Motive energy .....</b>	<b>8</b>
<b>5.1</b>	<b>Operating medium .....</b>	<b>8</b>
<b>5.2</b>	<b>Quality .....</b>	<b>8</b>
<b>5.3</b>	<b>Pressure .....</b>	<b>8</b>
<b>5.3.1</b>	<b>General .....</b>	<b>8</b>
<b>5.3.2</b>	<b>Maximum allowable pressure (MAP) .....</b>	<b>8</b>
<b>5.3.3</b>	<b>Design pressure .....</b>	<b>9</b>
<b>5.3.4</b>	<b>Working pressure .....</b>	<b>9</b>
<b>5.3.5</b>	<b>Structural test pressure .....</b>	<b>9</b>
<b>5.3.6</b>	<b>Minimum moving pressure .....</b>	<b>9</b>
<b>6</b>	<b>Actuator performance data .....</b>	<b>9</b>
<b>6.1</b>	<b>Minimum moving pressure .....</b>	<b>9</b>
<b>6.2</b>	<b>Operating time .....</b>	<b>9</b>
<b>6.3</b>	<b>Displacement volume .....</b>	<b>9</b>
<b>7</b>	<b>Basic design requirements .....</b>	<b>10</b>
<b>7.1</b>	<b>Safety requirements .....</b>	<b>10</b>
<b>7.2</b>	<b>Actuator attachment .....</b>	<b>10</b>
<b>7.3</b>	<b>Angular stroke .....</b>	<b>10</b>
<b>7.4</b>	<b>Endurance of part-turn actuators .....</b>	<b>10</b>
<b>7.5</b>	<b>Leakage .....</b>	<b>11</b>
<b>7.6</b>	<b>Environmental conditions .....</b>	<b>11</b>
<b>7.6.1</b>	<b>Ambient temperature .....</b>	<b>11</b>
<b>7.6.2</b>	<b>Enclosure protection .....</b>	<b>12</b>
<b>7.6.3</b>	<b>Corrosion protection .....</b>	<b>12</b>
<b>7.7</b>	<b>Pressure connections .....</b>	<b>13</b>
<b>7.7.1</b>	<b>General .....</b>	<b>13</b>
<b>7.7.2</b>	<b>Remotely mounted pilot valves .....</b>	<b>13</b>
<b>7.7.3</b>	<b>Direct mounted pilot valves .....</b>	<b>14</b>
<b>7.8</b>	<b>Pressure connections for single acting actuators .....</b>	<b>15</b>
<b>7.9</b>	<b>Fail safe direction for single acting actuators .....</b>	<b>15</b>
<b>7.10</b>	<b>Structural safety factors .....</b>	<b>15</b>
<b>7.11</b>	<b>Position indication .....</b>	<b>16</b>

<b>8</b>	<b>Optional equipment .....</b>	<b>16</b>
<b>8.1</b>	<b>Ancillaries .....</b>	<b>16</b>
<b>8.2</b>	<b>Manual operation .....</b>	<b>19</b>
<b>8.3</b>	<b>Mechanical end stop adjustment .....</b>	<b>19</b>
<b>9</b>	<b>Conformity assessment .....</b>	<b>19</b>
<b>9.1</b>	<b>General .....</b>	<b>19</b>
<b>9.2</b>	<b>Type tests .....</b>	<b>19</b>
<b>9.3</b>	<b>Control of production process .....</b>	<b>20</b>
<b>10</b>	<b>Marking .....</b>	<b>21</b>
<b>10.1</b>	<b>Mandatory marking .....</b>	<b>21</b>
<b>10.2</b>	<b>Optional marking .....</b>	<b>21</b>
<b>11</b>	<b>Documentation .....</b>	<b>22</b>
<b>12</b>	<b>Part-turn actuator selection guidelines .....</b>	<b>22</b>
	<b>Annex A (normative) Actuator type test procedure .....</b>	<b>23</b>
<b>A.1</b>	<b>General .....</b>	<b>23</b>
<b>A.2</b>	<b>Test equipment .....</b>	<b>23</b>
<b>A.3</b>	<b>Test conditions .....</b>	<b>23</b>
<b>A.4</b>	<b>Test procedure .....</b>	<b>23</b>
<b>A.4.1</b>	<b>Initial tests .....</b>	<b>23</b>
<b>A.4.2</b>	<b>Endurance test .....</b>	<b>24</b>
<b>A.4.3</b>	<b>Final tests .....</b>	<b>24</b>
<b>A.5</b>	<b>Acceptance criteria .....</b>	<b>24</b>
	<b>Annex B (informative) Actuator selection guidelines .....</b>	<b>25</b>
<b>B.1</b>	<b>General .....</b>	<b>25</b>
<b>B.2</b>	<b>Selection parameters .....</b>	<b>25</b>
<b>B.2.1</b>	<b>General .....</b>	<b>25</b>
<b>B.2.2</b>	<b>Valve questions .....</b>	<b>25</b>
<b>B.2.3</b>	<b>Actuator questions .....</b>	<b>25</b>
<b>B.2.4</b>	<b>Ancillary questions .....</b>	<b>26</b>
<b>B.2.5</b>	<b>Environmental conditions .....</b>	<b>26</b>
<b>B.3</b>	<b>Actuator selection .....</b>	<b>26</b>
<b>B.3.1</b>	<b>General .....</b>	<b>26</b>
<b>B.3.2</b>	<b>Torque characteristics for rack and pinion actuators .....</b>	<b>27</b>
<b>B.3.3</b>	<b>Torque characteristics for scotch yoke actuators (e.g. symmetric system) .....</b>	<b>28</b>
	<b>Bibliography .....</b>	<b>30</b>