

# ISO 5211:2026-02 (E)

## Industrial valves - Part-turn actuator attachments

---

### Contents

Page

Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Maximum flange torques.....</b>	<b>2</b>
<b>5 Flange dimensions.....</b>	<b>2</b>
<b>6 Designation.....</b>	<b>5</b>
<b>7 Dimensions and torques.....</b>	<b>6</b>
7.1 General.....	6
7.2 Drive by key(s).....	6
7.3 Drive by parallel or diagonal square head.....	9
7.4 Drive by flat head.....	10
7.5 Drive by improved flat head.....	12
7.6 Drive by involute spline.....	13
7.7 Drive by bi-square.....	14
<b>8 Position of driven components at interface below part-turn actuator.....</b>	<b>15</b>
8.1 Drive by key(s).....	15
8.2 Drive by parallel or diagonal square head or bi-square.....	17
8.3 Drive by flat head.....	18
<b>9 Dowel pins.....</b>	<b>18</b>
<b>Annex A (informative) Explanation of calculations.....</b>	<b>19</b>
<b>Annex B (normative) Dimensions of keys and keyways.....</b>	<b>21</b>
<b>Bibliography.....</b>	<b>27</b>