

ISO 4126-1:2004-02 (E)

Safety devices for protection against excessive pressure - Part 1: Safety valves

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols and units | 5 |
| 5 | Design | 5 |
| 5.1 | General | 5 |
| 5.2 | End connections | 6 |
| 5.3 | Minimum requirements for springs | 8 |
| 5.4 | Materials | 8 |
| 6 | Production testing | 8 |
| 6.1 | Purpose | 8 |
| 6.2 | General | 8 |
| 6.3 | Hydrostatic testing | 9 |
| 6.4 | Pneumatic testing | 10 |
| 6.5 | Adjustment of cold differential test pressure | 11 |
| 6.6 | Seat leakage test | 11 |
| 7 | Type testing | 11 |
| 7.1 | General | 11 |
| 7.2 | Tests to determine operating characteristics | 12 |
| 7.3 | Tests to determine flow characteristics | 14 |
| 7.4 | Determination of the coefficient of discharge | 15 |
| 7.5 | Certification of coefficient of discharge | 16 |
| 8 | Determination of safety valve performance | 16 |
| 8.1 | Determination of coefficient of discharge | 16 |
| 8.2 | Critical and subcritical flow | 16 |
| 8.3 | Discharge capacity at critical flow | 16 |
| 8.4 | Discharge capacity for any gas at subcritical flow | 17 |
| 8.5 | Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000 | 17 |
| 9 | Sizing of safety valves | 17 |
| 9.1 | General | 17 |
| 9.2 | Valves for gas or vapour relief | 18 |
| 9.3 | Calculation of capacity | 18 |
| 10 | Marking and sealing | 19 |
| 10.1 | Marking on the shell of a safety valve | 19 |
| 10.2 | Marking on an identification plate | 19 |
| 10.3 | Sealing of a safety valve | 19 |
| Annex A (informative) | Examples of sizing calculations for various fluids | 20 |
| A.1 | Capacity calculations for gaseous media at critical flow (see 9.3.3.1) | 20 |
| A.2 | Capacity calculations for gaseous media at subcritical flow (see 9.3.3.2) | 22 |
| A.3 | Capacity calculations for liquids (see 9.3.4) | 24 |