ISO 4126-1:2004-02 (E)

Safety devices for protection against excessive pressure - Part 1: Safety valves

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and units 5

5 Design 5
5.1 General 5
5.2 End connections 6
5.3 Minimum requirements for springs 8
5.4 Materials 8

6 Production testing 8
6.1 Purpose 8
6.2 General 8
6.3 Hydrostatic testing 9
6.4 Pneumatic testing 10
6.5 Adjustment of cold differential test pressure 11
6.6 Seat leakage test 11

7 Type testing 11
7.1 General 11
7.2 Tests to determine operating characteristics 12
7.3 Tests to determine flow characteristics 14
7.4 Determination of the coefficient of discharge 15
7.5 Certification of coefficient of discharge 16

8 Determination of safety valve performance 16
8.1 Determination of coefficient of discharge 16
8.2 Critical and subcritical flow 16
8.3 Discharge capacity at critical flow 16
8.4 Discharge capacity for any gas at subcritical flow 17
8.5 Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000 17

9 Sizing of safety valves 17
9.1 General 17
9.2 Valves for gas or vapour relief 18
9.3 Calculation of capacity 18

10 Marking and sealing 19
10.1 Marking on the shell of a safety valve 19
10.2 Marking on an identification plate 19
10.3 Sealing of a safety valve 19

Annex A (informative) Examples of sizing calculations for various fluids 20

A.1 Capacity calculations for gaseous media at critical flow (see 9.3.3.1) 20
A.2 Capacity calculations for gaseous media at subcritical flow (see 9.3.3.2) 22
A.3 Capacity calculations for liquids (see 9.3.4) 24