DIN EN 15091:2007-03 (E)

Sanitary tapware - Electronic opening and closing sanitary tapware

Contents

Page

Foreword 5

Introduction 6

1 Scope 7

2 Normative references 9

3 Terms and definitions 11

4 General requirements and testing 11
4.1 Marking 11
4.2 Materials 12
4.3 Functions 12
4.4 Protection against pollution 12
4.5 Electric characteristics and requirements 12
4.6 Leaktightness characteristics 14
4.7 Pressure resistance characteristics 15

5 Requirements and testing for tapware 17
5.1 Scope 17
5.2 Dimensional characteristics 17
5.3 Hydraulic characteristics 25
5.4 Water hammer 32
5.5 Endurance 33
5.6 Acoustic characteristics 34

6 Requirements and testing for flushing valves for urinals 36
6.1 Scope 36
6.2 Definitions 36
6.3 Classification of flushing urinal valves 36
6.4 Designation 36
6.5 Dimensional characteristics 37
6.6 Hydraulic characteristics 38
6.7 Measurement of water hammer for urinal flushing valves 38
6.8 Mechanical endurance 39

7 Requirements and testing for flushing valves for WCs 40
7.1 Scope 40
7.2 Definitions 40
7.3 Classification 41
7.4 Dimensional characteristics 41
7.5 Hydraulic characteristics 43
7.6 Principle and verification of atmospheric pipe interrupters of WC flushing valves 43
7.7 Mechanical endurance 43
7.8 Acoustic characteristics 44

Annex A (normative) Recommendation for the design of pressure take-off tees 45

Bibliography 47

Figures contents Figure 1 -- Type 1 - Supply system with a pressure range of (0,05 to 1,0) MPa [(0,5 to 10) bar] 8

Figure 2 -- Type 2 - Supply system with a pressure range of (0,01 to 1,0) MPa [(0,1 to 10) bar] 9

Figure 3 -- Tap with visible body for horizontal surface 18

Figure 4 -- Threaded inlets of taps with visible body for mounting on vertical surfaces 19

Figure 5 -- Tapware with inlets and outlets aligned 19

Figure 6 -- Tapware with inlets and outlets at right angles 20

Figure 7 -- Mixing valves for horizontal mounting threaded inlet 21

Figure 8 -- Mixing valves for horizontal mounting, stud connection 21

Figure 9 -- Mixing valves with straight fittings 22

Figure 10 -- Mixing valve with excentric unions 23

Figure 11 -- Mixing valve with captive nuts 24

Figure 12 -- Mixer with opposed inlets 25

Figure 13 -- Supply circuits 26

Figure 14 -- Test circuits for tapware intended for Type 1 water supply systems 28

Figure 15 -- Mounting of mixing valves 29

Figure 16 -- Flow rate test apparatus for taps intended for type 2 supply systems 30

Figure 17 -- Test rig for water hammer test 32

Figure 18 -- Top-entry urinal flushing valve 37

Figure 19 -- Side-entry urinal flushing valve 37

Figure 20 -- Side-entry WC flushing valves 43

Figure 21 -- Top-entry WC flushing valves 43

Figure A.1 -- Examples of pressure take-off tees 45

Tables Contents Table 1 -- Identification of the clauses of this standard 6

Table 2 -- Conditions of use 7

Table 3 -- Performance characteristics to be noted if used outside the recommended operating range 7

Table 4 -- Summary of leaktightness tests 15

Table 5 -- Dimensions 18

Table 6 -- Dimensions of threaded inlets 19

Table 7 -- Dimensions of threads 20

Table 8 -- Dimensions of mixers 21

Table 9 -- Dimensions 24

Table 10 -- Dimensions of pipework 28

Table 11 -- Flow rates and test pressures according to application 31

Table 12 -- Acoustic groups 35

Table 13 -- Classes of flow rate 35

Table 14 -- Classification 36

Table 15 -- Threads 37

Table 16 -- Flow rate 38

Table 17 -- Dimension of the supply pipe 39

Table 18 -- Threads and outlet pipe 41

Table 19 -- Permitted thread lengths 41