

DIN EN ISO 15118-10:2024-02 (E)

Erscheinungsdatum: 2024-01-05

Road vehicles - Vehicle to grid communication interface - Part 10: Physical layer and data link layer requirements for single-pair Ethernet (ISO/DIS 15118-10:2024); English version prEN ISO 15118-10:2024

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	3
5 Conventions	3
5.1 Definition of OSI based services	3
5.2 Requirement Structure	3
6 System architecture	4
6.1 Communication layers	4
6.1.1 Architecture	4
6.1.2 Layer 2 interfaces	5
6.1.3 Communication media	5
6.1.4 Data SAP	5
6.1.5 Service primitive concept of OSI layered architecture	7
6.2 System requirements	7
6.2.1 Overview of basic signaling	7
6.2.2 EVSE	8
6.2.3 EV	8
7 Connection coordination	9
7.1 General	9
7.2 Overview	9
7.3 Plug-in phase	10
7.3.1 EVSE side	10
7.3.2 EV side	10
7.4 Initialization phase	10
7.5 Loss of communication	10
7.5.1 General	10
7.5.2 EVSE side	10
7.5.3 EV side	10
7.6 Sleep mode and wake-up	11
7.6.1 General	11
7.6.2 Entering the sleep mode	11
7.6.3 Wake-up	11
7.7 During a charge pause	12
7.8 Plug-out phase	12
8 Timing and constants	12
9 EV - EVSE communication initialization	14
9.1 Overview	14
9.2 Errors	14
10 EMC requirements	14

11	Signal coupling	15
11.1	General	15
11.2	Schematic of the coupling network	15
11.3	10Base-T1S requirements	16
	Bibliography	17