E DIN EN ISO 15118-2:2025-10 (E)

Erscheinungsdatum: 2025-09-19

Road vehicles - Vehicle-to-Grid Communication Interface - Part 2: Network and application protocol requirements (ISO/DIS 15118-2:2025); English version prEN ISO 15118-2:2025, only on CD-ROM

Contents

Page

Foreword vii

Introduction ix

1 Scope 1

2 Normative references 1

3 Terms and definitions 3

4 Abbreviated terms 7

5 Conventions 8
5.1 Definition of OSI based services 8
5.2 Requirement structure 8
5.3 Usage of RFC references 9
5.4 Notation used for XML schema diagrams 9

6 Document overview 9

7 Basic requirements for V2G communication 11
7.1 General information 11
7.2 Service primitive concept of OSI layered architecture 11
7.2.1 Overview 11
7.2.2 Syntax of service primitives 12
7.3 Security concept 12
7.3.1 Call flows (flow charts) 12
7.3.2 Certificate and key management 16
7.3.3 Number of root certificates and root validity, certificate depth and size 18
7.3.4 Support and application of TLS 19
7.4 V2G communication states and data link handling 21
7.5 Data link layer 26
7.6 Network layer 26
7.6.1 General 26
7.6.2 Applicable RFCs and limitations and protocol parameter settings 26
7.6.3 IP addressing 27
7.7 Transport layer 28
7.7.1 Transmission control protocol (TCP) 28
7.7.2 User datagram protocol (UDP) 29
7.7.3 Transport layer security (TLS) 29
7.8 V2G transfer protocol 32
7.8.1 General 32
7.8.2 Supported ports 33
7.8.3 Protocol data unit 34
7.9 Presentation layer 37
7.9.1 XML and efficient XML interchange (EXI) 37
7.9.2 Message security 40
7.10 Application layer 47
7.10.1 SECC discovery protocol 47
7.10.2 Vehicle to grid application layer messages 52
7.10.3 Application layer service primitives 52

8 Application layer messages 56
8.1 General 56
8.2 Protocol handshake definition 57
8.2.1 Handshake sequence 57
8.2.2 Message definition supportedAppProtocolReq and supportedAppProtocolRes 58
8.2.3 Semantics description supportedAppProtocol messages 59
8.2.4 Message examples 60
8.3 V2G message definition 61
8.3.1 General 61
8.3.2 Message definition 61
8.3.3 Message header definition 62
8.3.4 Message body definition 63
8.4 V2G communication session and BodyElement definitions 64
8.4.1 General 64
8.4.2 Session handling 65
8.4.3 Common messages 68
8.4.4 AC messages 99
8.4.5 DC messages 102
8.5 Complex data types 111
8.5.1 Overview 111
8.5.2 Common 111
8.5.3 AC 140
8.5.4 DC 144
8.6 Identification modes and message set definitions 152
8.6.1 Overview 152
8.6.2 Supported message sets 154
8.6.3 Selection of message sets 180
8.7 V2G communication timing 185
8.7.1 Overview 185
8.7.2 Message sequence and communication session 186
8.7.3 Session setup and ready to charge 191
8.7.4 V2G message synchronization with IEC 61851-1 signalling 200
8.8 Message sequencing and error handling 220
8.8.1 Overview 220
8.8.2 Basic Definitions for Error Handling 221
8.8.3 ResponseCode handling 222
8.8.4 Request-response message sequence requirements 227
8.9 Request-response message sequence examples 276
8.9.1 AC 276
8.9.2 DC 279

Annex A (normative) Schema definition 286

A.1 Overview 286

A.2 V2G_CI_AppProtocol.xsd 287

A.3 V2G_CI_MsgDef.xsd 287

A.4 V2G_CI_MsgHeader.xsd 288

A.5 V2G_CI_MsgBody.xsd 288

A.6 V2G_CI_MsgDataTypes.xsd 296

A.7 xmldsig-core-schema.xsd 305

Annex B (normative) Certificate profiles 310

Annex C (normative) Specification of identifiers 318

C.1 e-Mobility authentication identifier (EMAID) 318
C.1.1 EMAID syntax 318
C.1.2 EMAID Semantics 318
C.1.3 Calculation of the check digit 319
C.2 Electric vehicle supply equipment ID (EVSEID) 319
C.2.1 EVSEID syntax 319
C.2.2 EVSEID semantics 320
Annex D (informative) Mapping of ISO 15118-1 use case elements 321
D.1 Relation of identification modes and use case elements 321
Annex E (informative) Message examples 376
E.1 Value added service selection 376
E.2 EXI encoded message examples 378
E.2.1 SessionSetupRes message 378
E.2.2 ChargeParameterDiscoveryReq message (AC-based) 379
E.2.3 CurrentDemandReq message 379
E.3 Schedules and tariff information 380
E.3.1 Overview 380
E.3.2 Dynamic GridSchedule w/o SalesTariff over ISO 15118 V2G CI 380
E.3.3 “Time Of Use”-based SalesTariff with constant value for GridSchedule 382
E.3.4 “Time Of Use”-based SalesTariff with dynamic GridSchedule 383
E.3.5 “Consumption”-based SalesTariff with constant value for GridSchedule 385
E.3.6 Multiple SalesTariffs with different demand Limits in GridSchedule 386
E.3.7 Time of Use-based SalesTariffs including relativePricePercentage 388
Annex F (informative) Application of certificates 397
F.1 General information 397
F.1.1 Overview 397
F.1.2 Demands of the OEM 398
F.1.3 Demands of the secondary actors 398
F.1.4 Rationale for decisions in this document 399
F.1.5 Overview of the resulting certificate structure 401
F.2 Simplified certificate management in private environment 402
F.2.1 Overview (motivation) 402
F.2.2 Solution for private environments 402
F.2.2.1 General 402
F.2.2.2 Installation of a private root certificate into a vehicle 403
F.2.2.3 Charging in a private environment 403
F.2.2.4 Compromised certificate of a wall box 403
F.3 Use of OEM provisioning certificates 404

F.3.1 Introduction 404
F.3.2 Processes 405
F.3.2.1 Vehicle production 405
F.3.2.2 Vehicle Hand-Over 406
F.3.2.3 Contract Conclusion 406
F.3.2.4 Certificate installation 406
F.3.2.5 Certificate update 406
F.3.2.6 Component replacement 406
F.4 Security appliances and their associated certificates 407
Annex G (informative) Encryption for the distribution of secret keys 410
G.1 Overview 410
G.2 Ephemeral-static Diffie-Hellman key agreement 410
G.3 Key pairs 411
Annex H (informative) Message sequencing for renegotiation 412
H.1 Overview 412
Annex I (informative) Overview on XML signatures 419
I.1 Overview 419
I.2 Signature generation 419
I.3 Signature generation for secondary actors 422
I.4 Signature validation 422
Annex J (informative) Summary of requirements 424
Annex K (informative) Use of Multiple Contracts in ISO 15118-2 432
Bibliography 434