

ISO 19072-2:2007-10 (E)

Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods and general performance requirements

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Functional characteristics of mated connectors	2
4.1	General	2
4.2	Visual examination	2
4.3	Mating and unmating	2
4.4	Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer	2
4.5	Mechanical strength of the retainer in the squib holder	4
4.6	Combination of temperature/humidity/vibration	5
4.7	Coding	8
4.8	Polarization	8
4.9	Contact resistance (voltage drop), millivolt test	8
4.10	Insulation resistance	10
4.11	Withstand voltage	10
4.12	Thermal ageing	10
4.13	Opening and closing of the short-circuit	10
4.14	Short-circuit resistance	12
4.15	Rapid change of temperature (thermal shock)	12
4.16	Chemical fluids	12
5	Test sequences	12
Annex A (normative)	Sealed variant of the pyrotechnic device/initiator harness connector assembly	14
Annex B (normative)	Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly	16
Annex C (normative)	Variant without retainer of the pyrotechnic device/initiator harness connector assembly	18
Bibliography		19