

ISO/TR 14646:2007-10 (E)

Road vehicles - Side impact testing of child restraint systems - Review of background data and test methods, and conclusions from the ISO work as of November 2005

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Accident statistics	1
3 Side impact test methods for cars	4
3.1 European side impact test methods	4
3.2 US side impact test methods	5
3.3 Japanese side impact test method	6
3.4 Australian side impact test method	6
4 Child related properties of car side impact test methods	7
4.1 Boundary conditions for a CRS side impact test procedure	7
4.2 Door intrusion depth	7
4.3 Door intrusion velocity from ECE tests	8
4.4 Door intrusion velocity in car-to-car tests	10
4.5 Struck car acceleration and velocity change	13
4.6 Deformation profiles	14
4.7 Dynamic force-deflection characteristics of door interior	15
4.8 Door window sill height and distance to door trim	16
5 Requirements for the side impact test procedure	17
5.1 Test severity	17
5.2 Validation	18
5.3 Repeatability and reproducibility	18
5.4 Field of application	18
6 Historical overview	18
7 Current side impact test procedures for child restraint systems	20
7.1 ISO/DIS 14646 / TRL test procedure	20
7.2 TNO test procedure	23
7.3 TUB test procedure	23
7.4 ADAC test procedure	23
7.5 Australian Standard AS/NZS 1754 test procedure	23
7.6 Australian CREP test procedure	23
8 Conclusions	24
Annex A (informative) ISO/DIS 14646-1.2: ISO side impact test procedure for rearward-facing child restraint systems	25
procedure for forward facing systems	36
Annex C (informative) Voting results and comments received on ISO/DIS 14646:2003	39
Annex D (informative) Voting results and comments received on ISO/DIS 14646-1.2:2005	45
Glossary	49
Bibliography	50