ISO 26021-2:2008-07 (E)

Road vehicles - End-of-life activation of on-board pyrotechnic devices - Part 2: Communication requirements

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and abbreviated terms 2

5 Conventions 3

6 Pyrotechnic device deployment via on-board diagnostic architecture 3
6.1 Vehicle system description 3
6.2 Example of in-vehicle hardware and software required 4
6.3 Additional communication line (optional) 5
6.4 Requirements for the PDT 5

7 Relationship to existing standards 6
7.1 General 6
7.2 Application layer 6
7.3 Session layer 6
7.4 Application layer and diagnostic session management timing 6
7.5 Network layer 7
7.6 Data link layer 7
7.7 Data link layer 9
7.8 Physical layer 9

8 Deployment process 9
8.1 General information 9
8.2 System preconditions 9
8.3 Initiation of the communication between PDT and PCU 10
8.4 Deployment process description 11
8.5 Software provisions 19
8.6 Error handling and reaction 20

9 Communication with diagnostic services 21
9.1 Unified diagnostic services overview 21
9.2 Diagnostic session control (10 hex) service 21
9.3 EcuReset (11 hex) service 22
9.4 Read data by identifier (22 hex) service 22
9.5 Write data by identifier (2E hex) service 29
9.6 Security access (27 hex) service 30
9.7 RoutineControl (31 hex) service 31
9.8 TesterPresent (3E hex) service 35

Annex A (normative) Specification of the data identifier used 36

Annex B (normative) Deployment loop parameter definitions 41

Annex C (normative) Routine control parameter definitions 47

Bibliography 49