ISO/TS 22239-2:2009-12 (E)

Road vehicles - Child seat presence and orientation detection system (CPOD) - Part 2: Resonator specification

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 CPOD resonator components 2

5 Coil requirements 2

6 Electrical properties 3
6.1 Digital resonator protocol 3
6.2 Subcarrier bitstream 5
6.3 Modulation 7
6.4 Modulation parameters 16

7 Resonator timing 18
7.1 General 18
7.2 Power-up 18
7.3 Reset 18
7.4 Relevant timing and reset parameters 19

8 Electrical and environmental parameters 20
8.1 Absolute maximum ratings 20
8.2 Operating ranges 21
8.3 Storage conditions 21

9 CPOD resonator compatibility test 21

10 Resonator environmental qualification 22
10.1 Application profile 22
10.2 Common test parameters 23
10.3 Operating states 24
10.4 Parametrical test and parameter checking 24
10.5 Qualification tests 25
10.6 Electromagnetic compatibility (EMC) test 38
10.7 Electrostatic discharge (ESD) test 47
10.8 Magnetic field stress test 50
10.9 Qualification flow chart 51

Annex A (normative) CPOD resonator compatibility test set-up 52

Annex B (normative) CPOD resonator compatibility test parameters 58

Annex C (normative) Continuous parameter check 61

Annex D (normative) CPOD reference resonator 63