

# ISO 13064-2:2012-09 (E)

## Battery-electric mopeds and motorcycles - Performance - Part 2: Road operating characteristics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>2</b>
<b>5</b>	<b>Parameters, units and accuracy of measurements .....</b>	<b>2</b>
<b>6</b>	<b>Test conditions .....</b>	<b>3</b>
<b>6.1</b>	<b>Vehicle conditions .....</b>	<b>3</b>
<b>6.2</b>	<b>Atmospheric conditions .....</b>	<b>3</b>
<b>6.3</b>	<b>Track conditions .....</b>	<b>3</b>
<b>6.4</b>	<b>Rider and riding position .....</b>	<b>4</b>
<b>6.5</b>	<b>Driving selection mode .....</b>	<b>5</b>
<b>7</b>	<b>Preconditioning of the vehicle .....</b>	<b>5</b>
<b>7.1</b>	<b>Battery charge .....</b>	<b>5</b>
<b>7.2</b>	<b>Warm-up .....</b>	<b>5</b>
<b>8</b>	<b>Test sequence .....</b>	<b>5</b>
<b>9</b>	<b>Test procedures .....</b>	<b>6</b>
<b>9.1</b>	<b>Range at 80 % maximum speed .....</b>	<b>6</b>
<b>9.2</b>	<b>Complete battery discharge .....</b>	<b>6</b>
<b>9.3</b>	<b>Maximum speed .....</b>	<b>6</b>
<b>9.4</b>	<b>Partial battery discharge .....</b>	<b>7</b>
<b>9.5</b>	<b>Acceleration ability .....</b>	<b>8</b>
<b>9.6</b>	<b>Hill starting ability .....</b>	<b>8</b>
<b>9.7</b>	<b>Speed uphill .....</b>	<b>9</b>
<b>10</b>	<b>Presentation of results .....</b>	<b>9</b>
<b>Annex A (informative) Specimen format for test result sheet .....</b>		<b>10</b>