ISO 17458-4:2013-02 (E)

Road vehicles - FlexRay communications system - Part 4: Electrical physical layer specification

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviated terms 1
3.1 Terms and definitions 1
3.2 Abbreviated terms 10
3.3 Symbols 12

4 Document reference according to OSI model 13

5 Conventions 14
5.1 General 14
5.2 Notational and parameter prefix conventions 14
5.3 Important preliminary notes 15

6 Communication channel basics 16
6.1 Objective 16
6.2 Propagation delay 16
6.3 Frame TSS length change 18
6.4 Symbol length change 18
6.5 FES1 length change 19
6.6 Collisions 19
6.7 Stochastic jitter 20
6.8 Wakeup patterns 20

7 Principle of FlexRay networking 22
7.1 Objective 22
7.2 Interconnection of nodes 22
7.3 Electrical signalling 23

8 Network components 24
8.1 Objective 24
8.2 Cables 24
8.3 Connectors 25
8.4 Cable termination 25
8.5 Termination concept 27
8.6 Common mode chokes 27
8.7 DC bus load 27

9 Network topology 28
9.1 Objective 28
9.2 Point-to-point connection 29
9.3 Passive star 29
9.4 Linear passive bus 30
9.5 Active star network 31
9.6 Cascaded active stars 32

9.7 Hybrid topologies 32
9.8 Dual channel topologies 33

10 Asymmetric delay budget 33
10.1 Objective 33
10.2 Basic topology for asymmetric delay budget 34
10.3 Definition of Test Planes 34
10.4 Requirements to the asymmetric delay budget 36
10.5 Definition of maximum asymmetric delay portions 36
10.6 Other networks 43

11 Signal integrity 43
11.1 Objective 43
11.2 Mask test at TP1 / TP11 44

12 Electrical bus driver 49
12.1 Overview 49
12.2 Operation modes 50
12.3 Operation mode transitions 51
12.4 Bus driver - communication controller interface 53
12.5 Bus driver - bus guardian interface (optional) 57
12.6 Bus driver - host interface 57
12.7 Bus driver - power supply interface 61
12.8 Bus driver - level shift interface (optional) 63
12.9 Bus driver - bus interface 63
12.10 Bus driver - wakeup interface (optional) 77
12.11 Remote wakeup event detector (optional) 78
12.12 Bus driver behaviour under fault conditions 80
12.13 Bus driver functional classes 85
12.14 Bus driver signal summary 87

13 Active Star 88
13.1 Overview 88
13.2 Hardware overview 88
13.3 Signal timing 90
13.4 Active star device operation modes 98
13.5 Autonomous power moding flag (APM flag) 100
13.6 Branch operating states 101
13.7 Branch transmitter and receiver circuit 104
13.8 Active star - communication controller interface (optional) 105
13.9 Active star - bus guardian interface (optional) 115
13.10 Active star - host interface (optional) 115
13.11 Active star - power supply interface 115
13.12 Active star - level shift interface (optional) 118
13.13 Active star - bus interface 118
13.14 Active star - wake interface (optional) 119
13.15 Active star functional classes 119
13.16 Active star behaviour under fault conditions 120
13.17 Active star signal summary 122

14 Interface definitions 123
14.1 Overview 123
14.2 Communication controller - bus driver interface 123
14.3 Host 126

15 General features for FlexRay physical layer parts 127
15.1 Objective 127
15.2 Voltage limits for digital output signals 127
15.3 Input voltage thresholds for digital signals 127
15.4 ESD protection on chip level (HBM) 128
15.5 ESD protection on chip level (IEC61000-4-2) 128
15.6 ESD protection on ECU level 128

15.7 Operating temperature 128
15.8 Serial peripheral interface (SPI) 129

Annex A (informative) Application notes 131